1 9-11-68 set C/M over iron pipe glass. #520506

1/4 corner 5-6 Orion 10 5-12.

1-1876 Hunter P302 No 297 ∠6 N Neal.
corner gone - searched by digging in road, could find nothing.
Meas east line 6 77.97 - 8 lks short govt meas
- placed corner (not described) at 38.01 north 39.96 south no bearing
- meas west 39.87 S 89½° W. to stake set as center.

9-68 run line from N E 6 to S E 6 5144.07. R 5146.26
set C/M on line at 2501.77 then 2636.3. 2508.66
put pipe below broken glass etc. 2637.6
- corner line 3.5 East & traveled road N-S.
- corner lines with fence running west.
- " line 3 feet south fence running east.

over)

- Disc in power pole # 16980 east 27.9.
- pepsi cap in tele pole SSW 103.4.

4-1-77 Dug down to Kerr's C.I.M. under the packhorse. Set a CIM over and up to surface. Corner 4' E. of & N-S road and (see Pat) [Co Surv. wants to dig before Final acceptance] R.P.S. CSD 5. side pp # 16480 E 28.05

GOV. NOTES - OCT 6, 1853

~~OVER THE TRUE LINE~~ BET BETWEEN SECTIONS 5 + 6

~~VAR 10° 32' E~~

~~39.91 SET POST~~ gr. SECTION CORNER

~~BC - OAK 8 S 78 W 105~~

~~BC OAK 5 ALL W 142~~

S 9' E ON TRUE LINE BETWEEN SECTIONS 5+6

VAR 10° 29' E

38.05 SET POST AT gr. SECTION CORNER

78.05 TO SECTION CORNER