1-7-3-69 set C/M on ½"x2' rod on sec line & prop. measured. ± 20-77 "Correction of corner" set CIC/P² #520604 #1

Note: Cor stone Could be farther South Should dig again. R.B.

¼ corner 6-7 Orion 10 5-12 Found Stone 4-77

7-1876 Hunter P302 No 297 Ld N Neal.

See field Bk 1 p 142-145

Found orig stake remains - 1 B tree standing - SW. bearing did not quite agree so re-referenced as follows to stake 12" burroak S16½°W 153 Lks, Orig BT. S8°W 154 Lks & S 60° W 225

- 1/16 west set marked stake on line & prop mean 39.25 overran 4 links. thence 20.02 (1321.32) then 19.23 (1269.18) to SW 6. to orig stake found and tested by NW 8 tree - others gone. 2590.5

11-1877 Hunter P325 No 319 Ld 7 John Fitzpatrick etal.

found stake P302 set stone 2½ x 4/16 x 23

- meas east 39.97 to section corner stone.

2638.02 5228.52

1968 J Kerr. Meas center 7 north set ½" rod at 26 40/100 inch came 2' from N edge road in line fence south. Line at ② east from fence running North & center very good until just next to road indicating fence may be slightly west of corner at road end.
– also run & meas line C/M at 5-6-7-8 west to temp nail in line fence
North 2590.3 R 2590.5 2642.6 east to C/M. R 2638.
– on check of 1/16 road north 1269 from F.N. at SW 6 to ℄ road North R 2590.18
– dug with backhoe entire north half of road to ditch, at least 10' long 5' deep. found not even a pebble. Soil clean.
– random line from west on likely line came 4.75' S of rod set indicating stone very likely on south half of road. – 4' east of French telephone cable line 18" deep about 18" from south edge rock (Must hand dig. deep.

7-1-69 dug south half road by hand. 5' deep 4x5 wide found absolutely nothing. dug from fence line south east ac fence line 2642.6 from SE 6 R 2638.0 – finally at C/M at SW 6 at 5229.6 R 5228.5 see card # 2.

#520604 (#2)

Card #2 1/4 corner 6-7 Orion 105-12.
7-3-69. Meas west half of section line carefully again from rod set 2642.6 west of SE corner 6. to C/M set as SW corner 6. total mile 5229.6 R 5228.5
set C/M on direct line at 2638.6 R 2638.0 from SE corner 6. making line west 2591.0 R 2590.5
set C/M with 1/2" x 2' rod below & glass.
- corner came 4' east of start of fence south, but by proven numerous offset of main fence this 4' east bowed line with main line of fence. - corner also about 1'+ south center road surface as traveled.
Mt Dew cap in Power pole # 16513 4' W & South 35.4 over -

16 west set 1/2" x 2' rod on section line at point
distances 1321.6 R1321.3 west of CIM at 1/4 6-7
and. 1269.4 R1269.2 from 1/16 west to CIM & W 6.
RP 1/16. fire call post # 0686 18" S & W 4.7'
Center top of field corner post, fences S & W SW 34.5
Center power pole with red reflector on N side.
16520. SSW 65.1
Corner brass cap on west side farm drive south
2' north of south road fence running east.
4-20-77 Dug from Kerr CIM South! Finally found
Hunter's recorded stone 12.4 So. & 2.3' E of Kerr
CIM (removed). Corner on N. bank of the So. road
ditch and 6' E of fence line So. set and iron in the east
side of the stone and set a CIC 1p² at the corner. Corner 12' So. &
R.P. CSD E side pp # 11666 SSW 22.44

1/4 COR. 6-7 ORION 105-12 #520604 (2)

OCT. 6, 1853 - GOV. NOTES -
EAST ON TRUE LINE between sections 6+7
COURSE N 88° 34' E.
39.21 SET POST FOR QR. SECTION CORNER d4
BR. OAK 8 N 8½ E 225
BR. OAK 7 S 8 W 154
79.21 TO SECTION CORNER

MEASURED SOUTH ON WEST SIDE SECTION 7. FIND LENGTH of mile
ONLY 79.10 + FIND that CORNER to SECTION 7, 12, 13 + 18 +
TO 1, 6, 7 + 12 HAVE BEEN ESTABLISHED SOUTH of ORIGINAL MEASUREMENT

¼ Corner 6-7 Orion 105-12 #3

4-22-77 (1/16th West) Found wood stake 3' deep in clay on the West side of the driveway South. Set only a nail at the surface. Diggings cover line from ¼ Cor 6-7 to Kerr's CIM at W 6-7 and to Hunter's full measure from NW 6 at W 6-7. & Stake approx 11.8. So of Kerr iron.

4-28-77 (1/16th W) Removed Kerr's iron and set it 2.062 W of the stake found & on the line from (at J.H. located mission)
¼ Cor 6-7 to W Sec Cor 6-7 (At found corrected location) corner on the W side of the driveway So.
R.P.'s CSD in power pole SSW 54.88
CSD in corner post WSW 31.63