1 T-3-1968 set C/M over stone & each weight ①

section corner 8-9-16-17 Orion 105-12.

#S20905

6-1891 J Fraser P452 No 436 & 8 J. Campion

Corner long gone set stone 20"x2"x 8/15" as follows.

-meas ⅓ 16-17 (marked stake) north to ¼ 4-5 (stone in road 4"16"top) overran 10" set at 2640.2

-meas SW 8 to SE 9 (a boulder + stake aneed by Mrs Fisher etal) set stone at prop govt meas as south line 8 recorded as 2640 and south line 9 as 2648 each half. thus divided south line 8-5276.6 south line 9 & prop. shortage.

6-1902 R Fraser P710 No 624 & 17 Sidney Burnap. found limestone set P452 in line fence running east.

(over)

T.H. 3-18-71 Field Book 5 p.94 Unrecorded Survey-Sec 8 "G" gone also W.T. Trees gone reset ⅓ dist 39.97 NES 1⅓ miles Brass within 1 lk. at top of

- 1/16 west set stake 20.01 M & L. N 89°55'E
- 1/16 south set stake 19.99 1/8 M & L S 5'E

7-3-1968 J Kerr to relocate corner.

Meas line from 1/4 4-5 fence east, south to sec line fence each total .5' short of full 1/2 miles - set 120 D in center road west at 4-5-8-9 2' south of mail box about 1' t from east edge of traveled road. this too far south - 2666.5 north to fence east. - from 120 D south to section corner found 5285 Actual record for 2 miles 2640.2 which indicates road west way south of true location no corner ever set there.

Found recorded limestone with stones on 4 sides set each weight on each side with C/M Down 8" on top.

- Corner lies 2.0' ~~south~~ North fence east very near center road N-S
- Disc in corner post 2' south of east 35.0
- " " new cedar brace post 4' south of W 35.0
- southeast corner old shed LW 52.5

[redacted] SECTION CORNER 8-9-16-17 ORION 105-12

(2)

GOV. NOTES - Oct 6, 1853 - WILLIAM JONES #520905

80.00 chs. set post CORNER to sections 8-9-16-17

BUR OAK 5N 31W 45

RED OAK 7N 7E 23

AND DUG TRENCH

12-9-98

(520905) D SEC COR 8-9-16-17 105-12 ORION FOUND CIM DOWN 10" IN GOOD CONDITION CORNER FALLS 2' N OF FENCE EAST 1/2' EAST ℄ CR 129 AND 19' N OF FIELD ENTRANCE EAST & 31 1/2' N OF FIELD ENT. WEST.