4-19-77 CIC #521804 (1)

¼ corner 18-19 Orion 105-12.
11-1856 Hunter P17 no 27 S½ Sec 18.
used corner to set 1/16 east M & L 19.80
BT to 1/16 N 32° W 27½ lks – N 21° E 38½ lks.
Bearing north – N 1°45' W east N 89¼° E

6-1857 Hunter P32 no 51 N½ Sec 19. 19.72
used corner to set 1/16 + 1/64 corners east 9.86 and ~~17.92~~
BT to 1/16 N 56° W 30½ lks – N 11° E 35½ lks – S 35° E 32½ lks M & L.
bearing south N 1°23' W east N 89¼° E

Note meas don't jibe very good, no other records.

H.S. Gilman Book p. 20-21
indicates Stone at ¼ Cor. & meas E. 19.95¼ – 19.95¼
with Limestone shown at 1/16 Cor. E. on Plat.

4-77 Dug 8' diameter around corner post with 1½" pipe driven on the N. side. Found nothing

4-19-77 Set a CIC/p^2 .3' So of traverse point in pipe. Corner on the N side of the corner post and lines with fences N-W-S.

R.P. Sp. & CSD in N.W. side large blazed Red Oak SW 37.89

Spike in W side 17" Oak S. 39.95

1/16" East 4-19-77 Dug 3' N-S and 4' E-W centered on a point M&L from the pipe at ¼ Cor 18-19 to the corner post at Section Cor. 17-18-19-20. This point came approx. 8½' West of the pipe Kastler set here. Conditions poor. Dug through about 1' of slattered limerock mixed in black dirt - then hit bedrock. Found nothing.

1/4 CORNER 18-19 ORION 105-12 #521804 (2)

GOV. NOTES - OCT 6, 1853

TRUE LINE BETWEEN SECTIONS 18+19
COURSE S 89° 34E
39.87 SET qr. SECTION post
W. OAK 26 S 20 E 53
Hickory 5 N 16 E 35
79.87 To SECTION CORNER

SEE P 82 B for probable survey in this section (SE 1/4)