12-8-76 Set Pipe (Hold ~~for point on NW 28~~. #522104
Corner Final - Being used in both Sec 21 and Sec 28

1/4 corner 21-28 Orion 105-12 (1)

4-1900 Robt ~~Thos~~ Fraser P670 no 596 & 28 J white.
found long limestone in line fence south with top
broken off claimed by settlers to be where original
govt stake stood.

N 16 south found stone set by Hunter.
29 woodlot stakes set some B trees.

~~1~~ 10-12-76 Dug from 9' N to 12' S and 3' E and W
of t.n. set at approx John Keir's measure from E. Found
nothing. 3' of black dirt over silt over bedrock 6' deep.
10-13-76 Dug along E side of previous digging reaching
10' E of t.n. Also dug ~~of~~ SW of t.n. reaching 10' W.
Found nothing

12-8-76 Set 3/4" x 15" pipe as final corner by doubling the line and distance from NW 28 over the 1/16th corner post E of the NW corner Sec. 28. (We did not set anything at NW 28 due to post and rock when corner fell.)
Corner corner 20' E of center of road.
R.P.'s CSD E side Pp# 43693 NNE 39.43
CSD in fence post SE 25.60
Note: See T. H. Field Bk #14, P.17 For 1/16th W of 1/4 Cor 21-28.
Gov. Note - Oct 6, 1853
WEST ON TRVE LINE BETWEEN SECTIONS 21 + 28
VAR 9°55' E
40.07 SET QR. SECTION POST
ELM 8 N 23 W 24
MAPLE 89 61 E 30
80.14 TO SECTION CORNER

#522104 (2)

1/4 Corner 21-28 ORION 105-12

July, 1856 Thos. Hunter Pg. 12 No. 19 shows 1/4 Post.
1/16 west 20.18 chs. M&L - B.T.'s (S 32¼° E 33 lks.) & (S 63¼° W 37 lks.)
1/64 East 9.89 chs. then 9.89 chs. to 1/16 Cor, then 19.78 chs. to Sec. Cor.
B.T.'s to 1/64 East (N 55¾° W 4 lks.) & (S 60° E 25 lks.)
B.T.'s to 1/16 East (N 15¼° W 21 lks.) & (S 87¾° W 30 lks.)