X 5-27-77 ½" rod on stone c.i.m. inplace (1)
9-20-95 CHD SET 1" SQ PIPE W/CAP #522206

¼ corner 21-22 Orion 105-12.

5-1893 W Fraser P506 no 476 & 22 Dabzark Fox, Hasty.
found stake center road 2 rods west of Cemetery fence
on line fence running east also NE BT and SW BT
stump - placed stone 5x12x20 as corner, stake by side.
1/16 north drone stake 19.98¼ N&L. 1318.84
1/16 south drone stake 19.95 N&L 1316.7.
— east set stone on line to center 17.35⅛ (1145.18
16 then meas 22.30⅞ to center (a stone set).
1472.38

10-29-48 J Kerr B40 P27. 6
1" pipe meas west line 22. - 5270.27 (over)

Meas northerly could be 2636. as cemetery fence.
is at that meas.

Center Cem. cor fence post E 90.65
spud Power pole. NE 68.5

Cemetery Description - SW¼ 22 Book 129 page 378

Commencing 17 rods 32 lks. 301.62 east of NW cor of SW¼ 22.
the beg point - thence 16 rods 10 lks (270.6 east. thence South
9 rods 19½ lks (161.37 th W & N same as E & S.
something changed since layout (no date and N fence.
and modern road. → Possible LP: ⊙SD N side pp# 16782 ENE 131.85
Must check ⊙SD E side corner post N 37.78

5-25-77 17.35 1/8 ch East: dug with backhoe and found
2½" x 0/7 x 22" stone (broken in 3 pieces) 1' deep 3.7 S of and
1.2 W of T.N. Old stake on N side of stone. Drove ½" x 2'
rod on the E side of the base of the stone and laid
the pieces over the top. Corner 1' N of fence N and 3' N of ℄ (T.N. RP 7.5 W 3.8 N)

1/4 CORNER 21-22-ORION 105-12 #522206 (2)

GOV. NOTES - OCT 6, 1853
NORTH BETWEEN SECTION 21 + 22
VAR 10° 15' E
6.00 BROOK 4 LKS WIDE RVNS SE.
20.00 RIDGE N + S
40.00 SET QR SECTION POST
RED OAK 6 S 57½ W 85
RED OAK 6 N 68 E 92

5-25-77 Dug with backhoe and found the recorded stone with a stake on the East side 4' deep, 7½'W of ℄, 2' [redacted] of fence W, and ½' N of N. cemetery fence (chain link). Set 1" x 22" [redacted] pipe in the stake hole and a 1" iron on the W. side of the stone and bent over the stone. Set a ½"x2' rod at the surface. The Corner is .5' N and 1.35' E of the T.N. iron pipe (removed).

R.P.'s CSD N. side pp # 16777 NE 72.40 TH 6.92 S 6.10 E

CSD S. side pp # 16778 (anchor) SE 59.60

CSD S side telephone pole NW 36.66 stone 7.50 4.8 E

1/16th North - 8/14/78 - Found rod set in 1977 badly bent. Pulled rod and set a dragtooth in the hole from the RPs.

8-15-78 Removed the ½" rod set in 1977 and set a CIM over a drag tooth as the corner.

6-21-95 - FOUND CIM. 7' WEST OF ℄ CR #7. SET 1" SR PIPE W/CAP 39½' WEST OF ℄ CR #7 + 12' NORTH OF FENCE LINE WEST.

T @ REF PIPE

ART P.K. IN P.P. #16777 (POLE IN NE COR INT) TO ¼ COR 21-22 43° 06' 15.5"

TO ¼ COR 21-22 (CIM) VA 86° 52' 46" SLOPE 36.215 HOR 36.165

1/4 CORNER 21-22 ORION 105-12 (3)

#522206

9-20-95 CHD SET 1" SQ PIPE W/CAP.