/. 10-16-78 Set CIC W.C. #522304 (1)

1/4 corner 23-26 Orion 105-12

5-1877 Hunter P312 no 306 S26 L Shemeahorn.

Corner gone. both BTs standing reset stake from BTs.

1/16 east set stake M & L. 19.95 1/2. S 89° 55' W.

1/16 west set stake M & L 19.96 N 89° 33' W.

bearing 1/4 line south N 1° 20' W.

5-1877 Hunter P313 no 307 S23 A Hazelton.

Bearing north N 1° 10' W no mear.

GOV. NOTES - OCT. 6, 1853 BETWEEN
WEST ON TRUE LINE [redacted] SECTION 23 & 26
VAR 9° 48' E
40.00 SET QR. SECTION POST
LINDEN 16 9 10 E 34
ELM 13 N 3 W 92
80.00 TO SECTION CORNER

34
66
204
204
224

8-11-78 - 1/16th West - Found a 4½" x 6" x 16" limestone flint with the ground on the West side of the corner post to fence N-S-E

10-78 1/16th West : dug from 4' West to 17' West of the stone found by the corner post to cover Hunter's full measure from the N-S ¼ line in Sec 26. dug 5-6 ft. N-S on line of fence East but found nothing.

10-16-78 Set this corner at the intersection of the line from the S ¼ Cor 26 (set) over the Center 26 (set) and the line from Sec. Cor. 22-23-26-27 (set) over the stone found at the 1/16th East. The corner corner in a ldrge ditch so set a CIC 1p² Witness Corner 60.0 West on the section line. The

#522304 (2)

¼ Corner 23-26 Orion 105-12

10/16/78 continued: ¼ Corner lies with the main line of the fence East and for West. The Witness Corner is 4' N. of the E-W fence

RP's to W.C.:

CSD in fence post with Survey Marker Sign S.W. 7.0

Sp. & CSD in NE side 24" blazed Maple (on South side of ditch) SE 32.10

Spike in N. side 12" Walnut WSW 40.35

Spike in N. side 8" Walnut SW 51.30