#522505 (1)

6-12-73 set 1¼X24" solid iron with □ ends.
10-12-78 set CFC

section corner 25-26-35-36 Orion 105.12

4-1878 Hunter P336 No 330 S24-25 J Greenlee T Moore.

found remains old stake from stump of North and SW Btree.
set new stake in its place unmarked.
1/16 north set stake M&L 19.96 1317.36 to stake set M&L.
E/16 center SW¼25. set stake 20.05½ M&L. E-W 1/16 lines
1323.63

4-1893 H Fraser P505 No 475 SW¼25 J Moore.

didn't look for corner as snow was deep.
found 1/16 cor north and 1/16 cor between center & S¼25
reset 1/16 cor center SW¼25. but meas now 19.93½ M&L.
1315.71

over.

6-12-73 ran electronic traverse from east. see field books or traverse plat map.
- found corner post of property fences E and S. as near as possible to recorded. Hunter location. as H Fraser visited corner in winter or late spring.
- set 1¼" X 24" solid iron shaft with squared ends on N.E. side corner post of fences E & S.
for more see traverse notes or will add later.

GOV. NOTES - OCT 6, 1853 - WILLIAM JONES
80.00 chs SET Post CORNER CORNER to SECTION 25-26-35-36
RED OAK 10 N 30 E 50
" " 11 North 29 ✓
" " 8 S 18 E 9
" " 12 S 64 W 13 ✓

#522505 (2)

Section Corner 25-26-35-36 Orion 105-12

10-12-78 Set a CIC/P² on the square iron set on the NE side of the corner post to the fence N-S-E in 1973. Set a Survey Marker Sign and post 2.2 South. The corner is 7' NW of a 24" Red Oak

RP's: CSD & Spike in W. side (up 5') blazed 24" Red Oak SE 60.85

CSD & Spike in W. side (up 5') 10" White Oak SSE 49.90