#522506

1 6-20-73 set 1/2" rod between 2 stones. (1)
10-2-78 CIM

1/4 corner 25-26 Orion 105-72

5-1877 Hunter P 312 no 306 & 26 L Schemerhorn.
stake standing claimed by Mr. Schemerhorn as set by
a surveyor midway & lake on sec line, all BT trees gone.
accepted corner as is without further testing 1308.45
1/16 west set stake M & L to center stake 19.82 1/2 N89°53'E
BT trees to 1/16 cr 10" red oak N 86° W 12 1/2 lks. 8.25
6" white oak N 34° E 7 lks. 4.62

4-1878 Hunter P 336 no 330 & 24-25 J Krenlie T Moore.
found stake, checked line & mine proved to be 39.92 M & L.
drove new stake as corner.
1/16 south drove stake 19.96 M & L 1317.36
1/16 east " " 20.07 " N89°35'E
1324.62 ones.

1/16 center of W 1/4 25 drone stake M & L. 20.05 1/2 E-W 1/16 line.

4-1893 W Fraser. P 505 no 475 & 25 J Moore et al.
found stake P 336
1/16 south found stake 19.96 1/2
1/16 center of W 1/4. set stake M & L. 19.93 1/2 E W 1/16 line
to 1/16 corner found set P 336. which came on south side of river.
Could not find stake at center of W 1/4 25.

Lee Card #2.

6-12 to 6-20 1973 #522506

electronic traverse of section 25, see field book and plat map of traverse.

"Created" corner by results of traverse

area in steep gully type wash area with slight delta island at bottom of run where corner comes.

- set 1/2" rod between vertical limestones in permanent pasture lands, Common lands all around corner.
- a property corner at corner of woods lot line south some several hundred feet. No record of this.
- for mean north and south computed see field books.
- some dark mixed soil came near corner area

over

RP 1/4 25-26 Orion.

11.5 ENE to 20 D on N side 18" Maple.
on west side of flood water ditch section

85.7 NNW to 20 D on N side Southerly of
Turn ash

7/13/77 Mn/Dot RP's to above.
CN+D in 24" Maple (N. up 1.0) NE 11.56
CN+D in 15" Hackberry (N. up .5)
SE 35.68
CN+D in 19" Maple (NE up .6)
SE 53.76

GOV. NOTES OCT 6, 1853
NORTH BETWEEN SECTIONS 25 AND 26
VAR 10° 35' E
5.98 W. OAK 6 IN. diameter d 30
40.00 SET qr. SECTION post
RED OAK 12 N 35 E 35
RED OAK 79 78 W 92
65.00 ENTER dry bottom + d 80
good timber S.E.
67.25 STREAM 25 LKS WIDE RUNS d 70
S.E. & ENTER WET PRAIRIE
80.00 SET. post CORNER to SECTIONS 23-24-25-26 LEVEL
BR. OAK 15 N 15 E 1310

#522506 (3)

1/4 Corner 25-26 Orion 105-12

10-2-1978 Dug and found 2" diameter stake 12"+ long reaching into clay. Also found a 2" x 10" x 12" limestone standing 2.0 South and 1.0 East. Set a CIM over a 3/4" x 12" rod driven in the stake hole and set the stone on the East side of the monument. This corner is 14.88 North and .23 West of the corner set in 1973 (removed).

R.P.: Spike and CSD in N.W. side of blazed 21" Maple NE 44.5

Spike and CSD in SW side blazed 19" Maple ESE 12.57

M.H.D. Disc in root on E side 17" blazed Maple SSE 67.73

Set a Survey marker sign and post .9 East.

1/16th North 10/4/78 Found two limestones, a 1"x10"x16" and a 2"x12"x10" standing side-by-side on the South side of the E-W fence 10½' West of the corner post to the fence So. See Drawing for Location - these were not M&L.

10/6/78 1/16th South: Dug from a point M&L between ¼ Cor 25-26 (found) to the nor to the corner post at Sec. Cor. 25-26-35-36 West for 6' by 2'+ N-S. Found nothing