#530204 Card # 1

7-29-68 set short C/M over sash weight, glass, lime - stone pieces.

1/4 corner 2-11 Pleasant Grove 105-13.

No records —

8-1940 J Kerr B 20 - P 62-65. L 2-3-9-10

run line set 1¼" pipe broken glass N 64 E 2640.52.
some glass well below ground around pipe.

10" white oak marked L 1/4 2 N 10¼° E 47.1

7" " " " " N 57°30 E 29.2

7-26-29, 1968 J Kerr to reload corner.
run line from N 1/4 2 over center - mine line
found pipe & glass in open bean field.

over

Meas from center 2621.1 John 2619.62
shell rock within 2' set cast weight in place & 1¼" pipe with short C/M over weight. corner 1 foot deep.
— pub & 20 D South side 18" white or burr oak blazed AZ 85°5' 59.95
— " " east side 12" burr oak used blazed slope meas.
as terminal for fences north and west AZ 140°16' 46.8
— 1¼" pipe driven to rock, up 6.6' on exact N-5¼ line north 44.25

1/16 corner between center 2 and 1¼ 2. set ½"x18" rod on line and midway 1310.55 — corner comes within 2' of east edge road surface — 95.5' to center huge rock on north side farm drive — 82.0 to center 20" oak about 15' south of east

Card # 2

1/4 Corner 2-11 pleasant Grove 105-13

#530204

May 19, 1854 Gov't Notes.

West on true line between 2 & 11 Var. 10° 8'

40.00 set quarter sec. post

Br. Oak 8 N 45 E. 99 lks. = 65.34'

Br. oak 7 S 65 E. 106 lks. = 69.96'

80.00 section Corner

Pleasant Grove 1/4 corner 2-11

Govt Notes on back