Corner now No Good - NSE. 2-3 to be moved East + North

7-26-1968 set C/M over 3/4" x 30" pipe and pottery with green 2" pipe up 5' and large boulder south of pipe.

1/4 corner 2-3 Pleasant Grove 105-13. #530206

9-1884 Hunter P 392 no 383 S3 W Pierson.

Corner gone, in open cultivated field.
set temp stake on N-S section line at gent meas.
- meas north 39.28. 2592.48.
- 1/16 south set stake at 19.82 1/2. 1308.45 N 1° 8' E
- 1/16 west set 3x10x18 quarry stone 20.05 1/2 M&L. 1323.63. Due east

---

8-1940 J Kerr B 20 P62-65 Secs 2-3-9-10.
set long 3/4" bolt on line and perp gent meas.
- 1/16 north set 3/4" iron bolt at 1308.46 then 1284.96. To NE 3
total 2593.42

- 1/16 south - meas 1308.46 M & L ~~total~~ ? 2618.72
record Hunter total north 2592.5 - south 2616.9.

7-25-68 J Kerr found rod in open field, set
C/M (12" deep) over 3/4" x 30" pipe (1/16 corner 4' west true line
- 1/16 north 1307.5 to rod, found, then 1285.1 to NE 3.
RP 1/16 north - 16" bur oak east in fence 12' - 22" bur oak east in fence 30'
corner lies 4" south in fence with 2" iron pipe up 5' S. side
RP 1/16-2-3 1/2" pipe up 8" 20 rods west on E-W 1/4 line of sec 2.
- south peak Backbach barn roof AZ 329°16
- east peak roof main part house AZ 293°37
- south peak barn roof AZ 265°03

1/16 east set pipe midway 1317.42 - 30' north of true corner
as corner in ravine filled with junk.
- meas west to 1/16 fence running north 1307.5 R. 1223.63

Pleasant Grove 1/4 corner 2-3 #530206 (2)

Govt notes on Back

Cor' Wells M.G. Karrick 1851 North Random 203
40.00 Stl & stmp Std post
South on true line between Std 203
39.63 Stl 1/4 Std post
Bur Oak 10 Sl½ W127
Bur Oak 10 Sl½ E 290