X ~~8-8-64 set C/M orig 3/4 x 12" pt. by line & brass~~
~~9-28-71 pulled C/M set red 25W 66N as cor~~
section corner 3-4-9-10 Plea Grove 105-13.

1-1894 Jr Fraser P542 no 503 S4 L. Nichols #530305
found stone with stake by side, claimed by Mr whiting
that stake was orig stake and that he himself placed stone.
— east set stakes every 10.01 to S 1/4 3 a stone found

2-1892 Thos Fraser P470 no 451 S10 Goodwin, Campion
found stone partly lying down. Mr. Millet claimed he was
with Hanks when stone was set by orig stake.
— Meas south 39.69 1/3 to stake set N & L.

9-1907 Armstrong P112B S4 Michael McConnell.
found stone with Blue blackoak S 77° W 2'3" left as found (24)

1/16 west set limestone 3x12x30 M&L. 20.14. N89°54E
Corner 18' north of E-W fence.
- north. 40.20 to 1/4 corner which has a. 3x16x25 quarry stone south of it as E corner 25 acre plot N westerly.

5-1900 Robt Fraser P676 No 601 L 9. Ed Campion.
found stone claimed by all to be "right" corner.
- Meas west 20.04 1/2. to stake driven M&L to stone L89°30W.
- 1/16 south set stake 19.94 3/4 M&L. L 37 1/2' E
- 1/16 center NE 1/4 9. drove stake M&L 19.81 3/4 N-S 1/16 line

---

6-1917 J Kerr P 266 B. L 10 - 24 Haney.
found stone 2.4' east of tree. - 2640.7 east to 1/4 stone.

1965 Corner in 8' road cut. gone.

#530305

Card #2 Sec cor 3-4-9-10 Pleas Grove.

8-8-69 as corner in 6 or 7 foot cut run line in from west. deep impregnable gulley between corner and 1/16 corner west, 2 deep ravines between 1/16 corner and 1/4 4-9.
-found 1/4 cor 4-9 - triangulated 1076' over gulley found. large 1/16 corner part leaning SE to have its base exactly on mean & line believed by record etc to be where large 1/16 stone sat. set slim rolled rod (about 1/2" with boulder stone on N side of rod as 1/16 corner 1324' from West cor 1/4 4-9. this made N-S line of section corner in exact line fences E & W as it was when stone was in place over-

set C/M over 3/4 x 12" reinf rod at 1322.7 from 1/16 west on line. allowed 1.3 short to balance our more accurate measure against old meas across gully.

~~-21.3~~ east To 18" blazed burr oak natural scar on N side
~~-45.0~~ SW to pipe cap in power pole # 17375
~~-103.25~~ SSW to small natural scar on E side 14" long ash.
- 62.7 WSW to center 22" pine easterly of 2 large pines set 20 N of road edge this point about in center large root running south. corner lies about 5' east of center road north and fence south. which is declared not in orig place.

2646.2
1323.5
1322.7

See Card 3 for 1971 resetting of C/M corners

Card # 3 Sec. Cor. 3-4-9-10 Pleasant Grove 105-13

9-24-71 Co surv. went to corner to run line north (3)
to test 1/4 3-4 now in doubt as to E-W. #530305
- found road graded filled over corner. All RPs gone
feet easterly of 2 large pines - dug and found C/M
top with stone over corner down 3.8' set 18" 1" conduit
on old C/M with C/M over it. Re referenced.
~~61.52~~ W to 2" piece of chrome childs baton under fence.
~~62.75~~ 54.04 10' S of W to 20" D N side center base of 22" pine.
~~55.67~~ Tree orig witness left.
~~55.95~~ SW to scrib nail in no plate 7" pole ± 41102.
~~25.7~~ 51.7 E to 9 reca cap S side corner post level.
33.13 this post may lean further east and no brace now in place.
Corner 24" N ends road running east?
" center of fence running south some 150' S. and road north.
over

Corner now lines E edge traveled road running north.
May search for stone 825' South of 1/4 3-4.

9-29-71 Meas from east area 1/4 3-10 found thrasher Cylinder bar at 1/16 meas. 1320.8. R. WF. 1321.32 JK. 1320.35
Meas from Cylinder meet to C/M very short. 1313.8
— also found true 1/16 corner meas. .8' North and 4.4 W of corner set as 1/16 8-1969. by J Keir. - removed corner set iron pipe bowder and old car jack by 1/16 3x12x30 L Stone which now lies near 5' west of Corner of fences E & S.
- removed. both C/M's and iron below & set new corner (3/4 x 14" iron) marking below. set 7.5 W 1.6 N of old C/M location. final RPs in red on reverse side of card. - Meas east final 1313.8 + 7.5 = 1321.3 OK recds.

Card# 4 3-4-9-10 Pleasant Grove 10 5-13 (4)

8-1968 Meas from 1/4 4-9 as found (set CIM) east.
#530305
Not Too positive B 98 ℓ 77
set 1/16 hollow iron tube with stone boulder on N side at
1323.5 east of 1/4 4-9.
- Cont east on triangulation 370.85 base 1076' length.
to 2175.0 Cont east set CIM as 3-4-9-10
on line over 1/16 as set at 2646.2 making east 1/2 of
this section line a little less. (Meas. near 1323.5
but believe E 1/2 a little short.

---

as 1/16 west 9-29-71 found .8' N and 4.4 W CIM was
reset. 7.5 W and 1.6 N.
Meas W bon. 2646.2 - 7.5 - 2638.7 Needs Zaging.
R Ch Arm M&L 1329.24 R Fraser 1322.97

Govt Notes M.G. Karrick 1854

80.00 Std pos for corner to Sec 3, T1, R7E

Black Oak 15 N 37 E CCO

Dug trench

4-29-80 Set CIM on 3/4" iron set in 1971.

C.S.D in pp# 41102 SW 51.80

2' East of ℄ rd North

1.6 North and 7.5 West of Kerr Corner