1

8-6-69 set corner and meander corners 143' N - 143' W on lines.

4-12-1976 Set 16" CIM over 3/8" x 15" rod

1/4 corner 4-5 Pleas. Grove 105-13

#530406

7-1956 Hunter P 13 No 21 d 1/2 S 5

used corner - meas. west 20.05 to center.

7-1907 Armstrong P 112B d 4 Michael McConnell

set temp point M & L. 39.98 1/2 for line east 2637.7


Bearing N 0 d E (1°10' E) bearing E N 89°57 E

(Note) illegal to set this corner now

8-5-69 J Kerr run aerial line direct. set 120 in center road in line fence N as assumed corner line comes 3.17' east of 120. ÷ Meas 120 north to N 4-5 2621.38'

8-6 Meas 120 south to d W cor 4 2639.6. Goot meas calls for 2640 - 1320 - 1299.55' - set corner 1/2" x 14" rod. on line at 2640.82 south - 1320.42 + 1299.75 (2620.17) north

set ½" x 2' rod as meander corner 143' north down 12" outside RW of highway 90 - rod corner 5.3' NE of top of RW sign post on apprx parallel to highway 90.
- set ½" x 2' rod as meander corner 143' west on exact line to stone found as ¼ 5-6. which corner near middle to road. - 62.06 SW to tele cable post
31.75 About 10' W of N to pepsi cap in west side power pole # 17409.



9-23-71 found witness corner - re set corner for use in line running east. set 3/8" x 14" rod. in dited section of SW by bound lane.
38.33 SE by to closest meas of W by edge conc of SW bound lane
58.5 4' E of N to edge RW marker post.
4-13-72 set CIM over 3/4" x 15" rod set in 1971 Lee Taylor corner in N. ditch of I-90. Took no additional R.P.'s

Pleasant Grove 1/4 corner 4-5 #530406 (2)

Gold notes on Back

4-22-1980 Set a Survey Marker Sign and post on the NE side of the CIM.

Govt Works M.G. Karrick 1854 North Kansas
40.00 Std temp 1/11 Std. post
S 0° 6' E on true line between Sect
4 & 5
39.69 Std 1/11 Sect. post in Mound
with 1 Trench & pits, Stake, planted
Osage Orange Sect N. E. & S. W.