1 11-11-13 found recorded limestone. down 6" ①
7-3-75 S&F C.I.M. over stone with flat iron on S. side
section corner 8-9-16-17 Pleas. Grove 105-13.
#530905
5-1856 Hunter P4 no 7 L 17.
used corner to set
-1/16 south M&L 20.06. 132B96. 1/16 north M&L 19.91.
1314.06

9-1886 Hunter P415 no 404 L 9 L Burnett, L. Leach
found remains of old stake in road near corner of fence.
set stone in place of stake
1494.9 1164.9 = 2659.8 N 89° 25 E
-east set cedar stake 22.65 then 17.65 to L 49 stake found
1316.37
-1/16 north found old stake M&L 19.94 1/2. L 1/2° E

11-1886 Hunter P417 no 406 L 16 P. Redmond, W Levan
found stone P415. no mark.

4-1895 W Fraser P565 no 518 S 16 C Russel, L Tyler found stone set by Hunter P415.
No meas - line south to SW 16 has slight kink.
S 1/2° W to 1/4 16-17 then S 1° W to ~~S E~~ cor 16.

3-6-73 ran traverse from 1 point to E 1/4 8, W 1/4 8, nail at 1/4 8-17 and 1/16 fence N and point near section corner S E 8. ground snow packed and frozen hard.
4-11-73 walked to corner area 3' ± snow most places.
Meas from C A.R.#1. to stone found quite easily.
2681.± with 1/16 fence at 1356 Midway 1340.5
Record projected 2678.3 - no doubt of corners. limestone 16" high with 5"x8" face coming to fairly wide point.
1/16.0 WNW To 6"D traverse nail.

Card # 2. 8-9-16-17. Pleas. Grove. 105-13 #S30905 (2)
4-25-73. drove to corner put several irons near stone. took two trees as B trees.

103.75 S to 20 D Nail W side center 28" oak.

116.4 ESE to 20 D S side huge boxelder.

corner does line very well with fence east some 150'± east.

7-3-75
Drove to corner - straightened stone and placed a flat iron on the South side of the stone - set a C.I.M. over all.
Corner falls 1' west of corner post for fences E.-W. & South. Took New R.P.'s. over

C.S. disc & spike on E. side 31" OAK S.E. 125.6
spike on W. side 20" OAK. S. 104.1
Spike South side 20" Boxelder E.S.E. 116.6

Gov't Notes M.G. Karrick 1854

80.00 Std post for Cor to Sec'd 8, 9, 16 & 17

Black Oak 12 N 34 E 3.12

Bur Oak 10 S 68 E 4.13

May, 1856 Thos. Hunter pg 5 No. 8 used Sec. Cor.
1/16 North 19.91 chs. m&L to 1/4 post.
1/16 South 20.06 chs. m&L to 1/4 post.