1 Found stone 4-6-72 #531005 (1)

Corr 3-13-75

section corner 9-10-15-16 Plear Grove 105-13.
9-1876 Hunter P305 no 300 & 9 L Bennett

orig stake gone, but all B Trees either standing or stump plainly marked set new stake deep to protect from river overflow. — 1/16 north set stake M & L 19.93 line W. (1315.4)
also stake at 8.72 then 11.21 to above 1/16 cor. line E
(575.52) (739.86)

6-1886 Hunter P 410 no 399 & 15 W Burgan, R Folsom.
found stake P305 set boulder with cross in center,
and section numbers chiseled in respective corners
1/16 east set stone & stake by side M & L 19.94 1/2 (1316.58) N 89°10 E staking line
1/16 south set stone & stake by side M & L 19.95 & 25' E line east.
(set stone 3 & above 1/16 stone 10.07 1/2 (671.55) then (1316.7) 19.77 1/2 645.15 (see Card 2)
1/16 center NW 1/4 9. set stake by parallel lines & mede same as section lines

11-1886 Hunter P 417 No 406 L 16 P Redmond, H Levan.
found stone with chiseling P 410.

2-1892 D Fraser P 470 No 451 L 10 J Goodman, J Campion.
found stone set P 410
– meas north 39.69 1/3 to stake set M & L.

11-1962 Armstrong P 70 B L 10 4 parties. typical Armstrong survey.
No meas, no descriptions of corners or lines.
plat shows stone at corner.
1/16 north shows iron bar with slike at W 410
Dbg gvt B trees 11" sugar S 41 W 85 lks 56.1
12" Hackberry N 24 W 55 lks 36.3.
13" Elm N 34 E 45 lks. 29.7
8" W Walnut L 58 E 38 lks 25.1

#531005 (2)

Card # 2. section corner 9-10-15-16.
Pleasant Grove 10S-13.

4-6-1972 Co surv - found 1/16 South stone/boulder with cross under fence running N-S, west fence of cattle lane, which lies about 3' south of 3 large pines running west) and 24' W to closest of 3.
- Meas north without line, came to river about 1030' S bank.
- found recorded boulder with cross & section numbers chiseled on stone at respective corners.
8" hackberry tree N 13° — 18" twin elm ESE 21'
- found E-W fence at prop line recorded as 9.77½ (645.15' north of 1/4 15-16 stone may be close to station, large red cedar post at corner.)

4-10-72 ran & meas line from stone section corner above south. - set pot 40D at 890 on flat bottom land 14' E of (5th) blazed 18" boxelder also nail on random at 990 lining fence W.

- found 1/16 stone at 1316.95 R 19.95 1316.7
22.55 E of stone or 1.71229' per 100'
- projected line to P.O.T at 1959.8 to search for prop stone at recorded meas of 2633.4 - 645.15 or 1988.25
- corner stone at 1988.25 should lie 34.04' west of random.
- " " " 2633.9 " " 45.1 west of true random.

4-17-72 ran & meas line from iron set 45.1 west to center 16 as Jkers 11-1939 found 1/16 iron at 1352.16 and center at 2682.6. making.
1330.44. Center to 1/16 iron (Jkers 1331.66).
- ignored stone at 9-10-15-16. and offset 30' west at 1/16 stone and stone with cross at woodlot 673.22 south (record Hunter 671.55) and prop line south to 646.8 (record Hunter 645.15) set iron as corner. this made. Mega west 1333.46. (Jkers 1331.66 in Nov 39). and line from Center 16 over 1/16 iron would came.
3.43 Sq iron - random iron over 1/16 iron came 3.43 S of center stone set 1/4 15-16 3.35 Sq iron. 646.8 Sq woodlot stone and on line, and stone and 1/16 stone north - to line up section stone would go east 18.73' (See 1/4 10-15

Pleasant Grove Section Corner 9-10-15-16 (3)
#531005

Card Notes on Back

Jan, 1864 P.C. Compton Pg. 79 No. 118 shows Section Corner used to set 1/16 south to Subdivide S.E 1/4 of N.E 1/4 of Sec. 16

Cook Watts M.G. Harrick 1854

80.00 Std post for cor 10 Std 9, 10, 15 & 16

Sugar 11 S 41 W 85

Hackberry 12 N 21 W 55

Elm 13 N 31 E 45

Walnut 8 S 58 E 38