#531105

X 7-26-68 set CM one orig stone and 1" iron stake (1)

section corner 10-11-14-15 Plea. Grove 105-13

9-1893 W Fraser P532 No 495 Do line S 11, E Russell.

found stake, tested stump S W B T. found 7-1968

set stone beside stake.

1318.68

-1/16 east set stone and stake M & L. 19.98 then

drove stake 9.99. M & L between above 1/16 & 1/4 cor.

1-1894 W Fraser P 543 No 504 S 15 John Clark estate

found stone and stake.

-1/16 south drove iron stake M & L 19.87 1/2

see 1/4 10-15 for plat. (See 1/4 14-15 for 1/16 S).

8-1940 J Kerr B 20 P 62-65 & 2-3-9-10

found recorded stone packed in stone. 2x4x18.

notch in 10" elm	NE	49.95	See B-8
Center 4" ash	& W	70.6	P 19621
Center 9" red oak	W	37.8	
corner 3.5' W & road	S 2 42.75	from dec cor 1 mile N.	

7-1968 J Kerr found stone riser put by Mr Yates which checked with 1" iron shaft by stone 3½' below accepted shaft as corner. set sack weight over shaft below C/M with large limestones on east & west sides.

Corner lies 100' south of fence west - 2'± west & road.

- Dec top 12" white oak / corner post east		28.7
- Knotch on root south side 18" elm	ENE	50.2
- Natural crease in 20" white oak	NE	84.05
- Gap in power pole no 13195 - 5' north of west		41.1

= Made east in pasture & search for corner. 1319' ± to fence N-S found rod by post and Tree by power pole 8-1968

Section corner 10-11-14-15 Pleasant Grove 105-13 12

#531105

Corner Notes

50.00 Ore pole corner to sections 10-11-14-15

White Oak 15 S 40 W 21

Aspen 8 N 65 W 57

Aspen 12 N 64 E 31

White Oak 14 S 66 E 50

1-22-85 McClain found CIM. Measured 2629.99
West to drag Stake a 1/4 Cor 10-15 and 1310.31
North to 1" pipe @ 1/16 North. Surveyed SE1/4, SE1/4, SE1/4
Sec 10