1 5-24-72 set 1"x4' iron as corner from line & meas's
corr 3-13-75 #531505 (1)

section corner 15-16-21-22 Plea Grove 105-13.

6-1886 Hunter P410 no 399 S15 W. Burgax, R. Folsom.

Corner comes on side steep bluff slope. stump of SW BT left set temp point only. Impossible without special tools to set corner.

- Meas north 39.90. 2633.4 S25'E.
- 1/16 east set stake M & L 20.041/2. 1923' S89°5'W.
  to S 1/4 15 set M & L
  BT above 1/16 cor - 6" white ash. S77°W 19 1/2 links. 12.87
  6" " " S18°E 26 " 17.16

4-1895 H Fraser P565 no 518 S16 C Russell, G Zylor.

relocated corner. as in 2633 3/4 410.
- meas north. 39.90 to corner P410.
- 1/10 west set stake M & L 20.08. 2645.28

A-6-72 Co surv found engraved stone at 9-10-15-16. used as 00 for line and meas south - found 1/16 stone at 1316.95 with cross believed to be true corner set by Hanlen as I was vertical. and under fence
- stone was 22.55 west of random line 1316.95 R 1316.7
- found woodlot stone with cross at 1990.7. R 1988.8
- this stone. 43.64 west of random. should have been 34.04
- cont line south but offset 1.0' E to mea tree. set nail at 2634 R 2633.4
- cont line south with 2634 as 00 offset 60' E at Sta 750.0
- cont line to edge of bank of overflow area 2547.82

#531505

Card # 2 15-16-21-22 Pleasant Grove 105-13 (2)

5-22-72 found stakes at 1/4 21-22 positive and stake + small post at 1/16 north believe to be positive 1/16 corner north - meas Record of 1297.56 from center steel corner post in apriel. after finding stake at 1/4 21-22 .3 W and .8 N of corner post Zaped meas C I M set to 1/16 1296.64 apparently proving 1/16 corner. offset 10' E & Zaped line to edge bluff. 1203.03 then projected line to valley below at 29.5' offset east. 674.44 corrected. - this made point 580.22 S of section corner. - set back to true line - set 5/8" x 2½' iron on S edge sunk up 10" at 58.1 north of corner on line from S (not noted) set high up on slope within 5.0 6' of vertical limestone bluff. - slope very steep near impossible to ascend. direct to corner. 4.52 N to railroad spike on E side 8" very tall cottonwood tree 4 ft. 6.2 E to drag tooth on S side 12" mossy cottonwood tree W edge gully used. set 1" x 4' rod up 10" with green steel fence post on S E side.

Pleasant Grove Section Corner 15-16-21-22 3

Coal Veins on Back

Gov't Notes M.C. Karrick 1854 #531505

80.00 Sec Sec cor post 15, 10, 21, 22

Hickory 8 S 45 W 27

Elm 8 N 64 W 30

Elm 12 W 45 E 20

9 S 79 E 31

(3)