8-4-1964 set C/M by orig corner a 5' Twisted steel rod (1)
#531705

section corner 17-18-19-20 Place Grove 105-13
6-1886 Hunter P411 No 400 S18 Henry Witte
found marked orig corner by side of fence, B trees gone.
1/16 North found remains of stake set 1856 survey 106 from the witness tree taken then, proved to be N 0 L 20.07 also proof testing corners south. Due north
- Meas west 39.98½ L 89° E

11-19 39 L Kerr set 63" long twisted steel rod as corner at spot pointed out Mr Schully who remembers survey.

12-19 39 L Kerr used corner for line south
- Meas south 2621.37 to ¼ corner an iron shaft over)

8- 1964 J Kerr. set C/M to preserve corner location. pulled twisted rod. placed C/M in place, iron rod below.
RP 3/4"x 63" twisted steel rod up 38" west 0.5'

– 30D nail on east side 12" blazed oak in fence line N. 23.35'

– Hub & nail thru Red Brand sign nailed to 24" elm trunk which 4' above ground divides into 4 smaller trunks N20°E 4.2'

– Center 6" elm SE 18.35'

Court Notes M. G. Kanick 1551
80.00 Set post to cor set 17, 18, 19-20
Bur Oak 10 S 75 E 17'
" " " N 50 W 20'
Dug 1-20-64

207
.66
1242
1242
1342

134
66
804
804
868

#531705 (2)

Section Corner 17-18-19-20 Pleasant Grove 105-13

7-20-1979 Found Kerr CIM 1' East of Woven wire N-S fence units a 3/4" twisted rod (up 3½') Dist .45. Set a survey marker sign and pnt 1.0 South.

RP's: Spike E. side 13" Bur Oak in fence line North N 23.39

Spike and CSD SW side blazed 17" Bur Oak NW 38.83

The corner is 96' South of the junction of the N-S fence and pasture fence running NW.

(T. Hunter 1856 - Over

May, 1856 - Thos. Hunter page 3 No. 6 shows Sec. Cor.
1/16 North 20.07½ m&l Bearing Trees to 1/16 Cor.
(N 69 3/4° E 75 links) & (N 69½° W 139 links).

See blue book for history done!

12/17/62 CHO fd ¾" steel bar (twisted)
Rps 14" elm N 21° E 5.0'
12" oak N 30° W 38.9'
24" oak N 48° W 5.4'