8-4-1964 set CIM over ½" x 18" rod #531809 (1)
4-17-1973 found stone 5.1 N, 1.7 E pulled CIM set 1" iron.
¼ corner Center 18 Plede Grove 105-13
6-1886 Hunter P411 no 400 L 18 Cor 1 3-12-75 Henry Troitte
set stake at true inters. lines
1/16 north set stake N & L 20.02 N 55' E
1/16 south " " " 19.97 "
bearing To ¼ line running east & west N 89° 10' W.

Book 83 Page 24

10-1961 J Kerr placed ½ x 4' rod in tabacco Road survey placed same by lines from north & west where it best seemed to relocate corner without running out whole section.

8-1964 J Kerr crew - set CIM in place of rod to help preserve corner

over)

Corner lies in line with established fences W & South

Nail in hub- west side of blazed 16" red oak which is part of clump of 3 trees whose base lies at south edge deep sink hole, prevalent in this country.

2-28-73. set eye line offset Southeasterly 46.35 south 200' at W¼ 18. ran random line east on offset line fell 204.3 south of C/M set by J Kell at center 18. line fell 236.5 south of nail set in fence line at ¼ 17-18 on traverse. this point evaluated later as to M & L etc.

4-16-73 Meas without line south of C/M. set nail at 1300', found stake at ¼ 18-19 at 2624.5 R 2636.04

See Card 2.

Card # 2. Center 18 Pleasant Grove 105-13 (2)
#531809
4-17-73. Cont by running aerial and meas N-S ¼ line found C/M at center 18 to be 1.6 west of direct line and too far south for proportionate measure.
- dug and found boulder 5"x10"x16"± very vertical with long width E and west 5.1' north and 1.7 east of C/M. set 1" steel bar with hex top on NE corner of stone. (this is some NE of center of stone but best fits line and meas of entire line) removed C/M. but left rod below. took to RPS and corner very evident & in protected area by pot hole cave ins in area.

over.

final Meas North 26 36.91 R. 2642.64 stake 5.73
final Meas south 1314.8 M & L on 2629.6 R 2636.08. stake 6.44
– 1/16 south. set bolt and reference M & L which came
.68 E and .55 N of hole found in clay believed Hunters Corner.
RPS 52.5 NNW to tele clip hook on W side corner post
made from top of Red tele pole.
43.62 SW to nail in top of 4" Cedar post in Roadside.
Corner near center road due N of west gate post RR Tie.
Corner lies 6'± east of row of small maples with many sprouts.

---

May, 1856 Thos. Hunter Pg. 3 No 6 West line of East half
Sec 18 shows 20.01 chs 4 times. Bearing trees to Cen N.E. ¼
(N 37 3/4° E 88 links) taken N.E. ¼ (Bearing Trees → (N 21° E 277 links)
(S 49 3/4° E 320½ links) Cen S.E. ¼ (S 43½° W 143 links),