#531905 (1)

~~7-7-1965 set C/M over 1/2" x 2' rod.~~
~~10-7-91 Set 1" Sq Pipe/cap in blacktop~~
section corner. west 19-30 Pleas Grove 105-13.
east 24-25 High Forest 105-14.

No records.
1965 J Kell. run line from SW corner 31 to west 1/4 corner 19., an established accepted corner on township line
Set C/M at 3/4 of distance from west 1/4 30 to west 1/4 19.
this being equal and straight by original govt records.
accepting the corner at west 1/4 31 set by Minn Hwy Dept. as it lays. or. 2638.4 north of Twsp corner
next 2 miles 2631.3 each.

over RPS

center of top of steel corner fence post W ~~48.22~~
Disc in treated fence post in fence line (1988) 48.26
of west road fence running north NW ~~45.5~~
(1988) 75.38

corner lies in center north-south road.

corner very nearly lines with fence running west

Gate Valley

50.00 Set post [illegible] to [illegible] 19-24-25-30

B- Oak 10 N 5½ W 352

B- Oak 16 N 70 E 216

B- Oak 6 D 3½ N 266

6/1/89 SET 1" SQ PIPE/CAP ON LINE FROM PLASTIC DISC. IN SOUTHERLY TRANS. LINE POLE WEST OVER C.I.M REF PIPE IS ON S BANK OF FENCE RIDGE E. OF C.I.M
N @ REF PIPE TO W 19-30 CIM DIST. 110.53

SECTION CORNER W 19-30 PLEASANT GROVE (2)
E 24-26 HIGH FOREST #531905

6/1/89 Cont. TR REF PIPE 2RT HINES TO W 19-30
87° 32' 11", TO HINES 903.66'
10/17/91 County Surveyor set 1" sq pipe/cap in
& N-S CR # 20 in line of fence west