1 7-19-72 set 1/2" x 3' rod on line and recorded distance #532204 (1)
8-27-82 CTC/p² NOTE: see Unfinished corr. File

1/4 corner 22 - 27 Plea Drone 105-13.
2-1896 W Fraser P591 No 537 S22 L Wolf, C Decker, M Clark
Corner lost, no evidence or knowledge of any kind.
drone marked stake M & L. 39.91. 2634.06.
1/16 west. set stake marked 1/16 cor M & L. 19.94 1/2. 1316.37.
used corner to set center 22 an iron & wood stakes.

7-19-72. set prism on 21-22-27-28 and also set prism on point near corner post at 1/4 22-27. - set Zaper on rise near 1/16 corner between, distance 2633.21. R. 263274
- offset north 50' at point near 1/16 and 1/4 22-27
- Zaped line and ran transit line to fence at 180 acre line.

- projected line east to point north of 22-23-26-27.
Come 52.72 north at 5268.06 total.
- using proportions by H Fraser moved point at ¼ 22-27
.16 east and 1.36 south. drove ½" x 3' reinf rod as corner
final measure west 2633.37 R 2632.74
" " east 2634.69 R 2634.06
corner comes 1' east of corner post in line main fence.
South and west - found very old post stub near corner.
42.48 just N of E to 2 D on S side 18" barrick up 4"
1.3 W to 2 D nail on top of post
3.16 ENE ly to nail in copper plate on S side of
transmission line PP # 38065
Meas from C/M at SE 22 west to fence at 180 acre
line 1650' ± - wires of fence east almost exact line.
will search for center 22 - May change chain corner final as set.
found Cntr 22 11-30-77

Plummer Creek 1/4 corner 22-27 #532204 (2)

Good Notes on Book

8-27-1982, 1/4 Cr 22-27: Set CIC/p² .24 South and .09 East of the 1/2" rod (removed) set in 1972. Corner set at the intersection of the line from the N 1/4 Cr 22 over the Center 22 and the line from the SW Cr 22 to the SE Cr 22 by e.t.c. The corner .5' South of E-W fence and .5' East of the fence South.

RP's: Spike So. side pp # 38065' ENE 2.49
Conc. Nail E. side end fence post (with survey marker sign) to fence South SSW 1.39
Dug small hole around the corner location but found nothing.

Govt Notes M. G. Harrick 1854 East Random
40.00 Std temp. Stk. post 22+27
West on true line between Std 22+27
40.00 Std 1/4 section post 10°21'
Bur Oak 10 in N 55 W 11
Dug Iron

6-1886 (Old Fieldbook 14, Page 64) mad corner (no dirt) to set the 1/16 West, a stone, mudsill (20. chs) and on line. He also set the Center 22, a stake. He set a proper corner 11.14 ch North and 11.14 chs North of 1/16 West