8-17-1964 set C/M over limestone & brick. (1)
#532205
section corner 21-22-27-28 Pleas Grove 105-13
2-1896 W Fraser P591 No 537 S22 G Wolf, C Decker
found limestone set as corner, tested NE Mrs M Clark.
1/16 east set marked stake 19.94½ M&L (1316.37
1/16 north set "corner" 20.03½ M&L N 45° W (1322.31

J Kerr early survey run south line 21 found stone.
1964 J Kerr to place & preserve corners.
re run south line 21. found pipe placed as recorded as
1/4 21-28 at 2632.62 and limestone at double distance
limestone is .35' south of line projected from S 1/4 21 corner.
S 1/4 21 - found limestone & brick as recorded over)

NE corner house basement	N 30° W	85.15
Center 24" elm	S W	49.0
" 16" pine	S W	71.1
Elec pole.	S 10° E	48.9
West end 24" galv culv.	S 40° E	17.05
Elec power pole.	N 50° E	54.6

Corner lies partly in driveway to basement house in 1964

Gail Wolfe M.C. Karrick 1851

50.00 Std post for cor to Std 71, 72, 77, 78

Black Oak 5 75 W 278

Bl. Oak S N 55 W 87

" " S N 55 E 100

" " 17 5 1/8 E 157

#532205 (2)

Section Corner 21-22-27-28 Pleasant Grove 105-13

11-23-1982, Sec. Cor. 21-22-27-28: Dug up CIM. Corner 7' SW of the ℄ private drive running NW-SE.
RP's: Punch hole SW'ly end CMP across driveway SE 16.86
Punch hole NE'ly end CMP. across driveway NE 29.85