1 7-10-72 set C/M over orig stone and 15" rod. #532305 (1)

section corner 22-23-26-27 Pleas Grove 105-13

4-1895 H Fraser P563 No 517 S23 J. O'connor, H Burgan & Lowrie

Corner gone, dug rod square in road. Mr Dave Overland owns his fence running west was set on line corner but couldnt say how far to the corner post.

turn & meas line S E cor 23 to S W cor 22. 159.47

govt record 159.85

Divided as 79.81 5267.46 west 79.66 east 5257.56

set stone 4 x 4 x 15 with stake by side in line fence west

2-1896 H Fraser P591 No 537 S22 J wolf, C Decker thru M Clark

found stone P563

2634.06

- Meas west 39.91 to stake driven M & L
- Meas north see P 563. which is 1316.04
- 1/16 north set stone and stake M & L 19.94. to stone and iron stake set P 563 M & L 39.88. 2632.08
also P 563 not put down.
- 1/16 east set stone and stake M & L 19.91½ to stone 1314.39
set M & L. 39.83 2628.8

also 1/16 center SW¼ 23 stone & stake set inter lines

7-10-72 found. exact size stone 4x4x15 down 16" ± about 3' west of center of field road used by local landowner as field road. also found large wood stake on east side.
Meas east to 1/16 fence running north (from stone) 1317 ±
Meas east to stone found at ¼ 23-26 2627 ±

see Card # 2.

#532305

Card # 2. 22-23-26-27. Pleasant Grove. 105-13

RP to C/M set over stone found and ½" x 15" iron (2)

37.3 E to 20 D nail in hub on S side of north 16" trunk of clump of cherry tree.

35.3 SW to 20 D nail in NW side 12" burr oak.

– 1/16 corner north found pointed limestone near center of old unused road at 1316.5 R 1316.04.

set elec. fence post centering over stone with piece of old stake found on west side stone found. Bury

85.0 ESE to 20 D nail in hub on S side huge oak in open field. tree 108" circ. over 3' dia

15.08 E to cone nail on S side corner fence post. Corner lies 2.5' north of eye line of fence east. (was)

Will Zap. entire mile between sections 22-23 from road N.W.
7-14-72 Zaped from high point on road on N-S 1/16 line west
of section line., north to E-W 1/4 line where all points could
be seen. - using computations mean from 22-23-26-27 to
1/16 stone 1316.71 R 1316.08 and 1316.37 actual 1316.5±
and entire mile 5264. R 5264.32. - line projected from
2 known corners above would place 14-15-22-23 .41 east
- set point west of 1/4 22-23 area. which could be seen from.
Zap point (no closer point visible to anj. corner.
Computer point 728.13 west of point where 1/4 22-23 should
be. or 22-23-26-27 over 1/16 north and double 1316.5±

7-19. Zaped south line 22 on 50' random offset north at 21-22-27-28
corrected line at 1/4 22-27 set 1/2"x 3' rod on line and
2633.37. west - 2634.69 east. Corner as set good for occupation
lines.

Pleasant Grove Station ~~~~ 22-23-26-27 (3)

#532305

Good Notes on Back

Gov't Works Wm. G Kerrick 1851
80.00 Stl post in Mound with French
pits and charred stakes And Osage Orange
Stakes at Each angle from corners
to Stel 22, 23, 76, 77