X 11-20-1967 CIM set by Co Hwy Dept over old 1938 post
6-26-70 pulled CIM set out
#532404 (1)

1/4 corner 24-25 Pleas Grove 105-13

12-1884 Hunter P265 No 263 S 24 H Page.
could not find corner, ground frozen some. set
stone 2½ x 5 x 14 by from B trees as follows -
8" burr oak S 83° E 4.31 lks - 8" burr oak N 1° E 2.05 lks
2.84 ±

9-1885 Hunter P401 No 391 S 25 J Fait, J Baker, J French
D Brown.
set stone 6 x 8 x 18 from B trees standing -
found part of stone set P265 at exact spot on digging
- meas east 39.9 37.63 35.38 to 2' long burr oak stake set this survey
- meas west 40.07 36.44.63 ±/- 6 x 6 x 14 stone set in old post hole
1/16 south set stone 6 x 7 x 20 M & L 20.05 1323.63 ½ fairly well down.
ones)

9-1885 Hunter P403 no 392 S 24 J. Baker. H Lowrie
J. French.

found stone P401

1/16 west - set stone 3x3x14 M&L. 20.03½. 1322.31. line N
- meas east 39.93 2635.38 to corner P401.
- 1/16 north - set stake M&L 19.85¾ 2621.2 for ½ mile - set stake 100 lks W. as witness on line to center SW ¼ 24.
- 1/16. center SW ¼ 24. set stake at inters lines.

Co Hwy Dept - 1938 - 1967 found point of 1938 in new grading operation set C/M in finish grade. (68.05 68.05)
Desc cor fence past E 59.55 Sp 15" oak NE
" B307.0 " " SE 82.07 Meas north 2617.7 R2621.2
1965 " " 2616.43
found corner set 1938. no desc. set then from center 25 over 1/16 north.
later set re-rod. thru stake found. — doubl. 1923.7 1965-1322.21

#532404 (2)

Card #2. 1/4 24-25 Pleas. Grove 105-13

6-26-1970 Co surv. found CIM set by Co HD 1967. placed new iron corner below - set 1/2" rod riser.

Disc in corner post } Co ties. E 59.55
Sp in 15" oak } NE 68.05
Disc in fence post } SE 82.33

Repair cap in top Cor post of fence North 8" cedar E 59.58
3/8" x 8" nail on W side 20" maple SSE 126.5

corner lies .7' north of fence west, 1.0' south of fence east.

Cor Notes M.G. Kerr 1951 Found Rumbum 21+25
40.00 Std temp std post
West on true line between Std 21+25 10° 57' 180
40.00 Std 1/1 Std post Bur Oak 7 N 7 E 205
Bur OAK 8 S 75 E 284.46

7-20-82, 1/4 Cor 24-25: Dug with backhoe from hole ½" re-rod, East 4', South 3', North 3'. Found fill all the way to clean clay 4' deep.

7-23-82, 1/16 West: Found 2½" x 3½" x 13" pointed limestone down 8" and standing .6 SW of the C.P. to fences E-W-N. Brought stone up to surface and drove 3/8" electric fence post on E. side.

7-13 & 17-82, 1/4 Cor 24-25: Set a CIC/p² as the corner 1.69 South and 2.07 East of 5/8" iron in place (removed). Corner 1½' South fence line East and 2' East & C.R. 19 and ½' South of fence line West. This corner set on line from the 5 1/4 Cor. 25 (as set this survey) over the Center 25 and at T.H. prorated measure from the Center 25 (prorated against the measure from the 5 1/4 Cor 25 to the Center 25).