#532604 (1)

¼ Corner - 26-35 Pleas Grove 105-13

no apparent records.
T.H. 30 R/w Map (1950's) indicates some kind of Corner inplace or used was apparently at intersection of old roads E-W & N.
Ties To point used: Tel. p. - N.E. 59.6
P.P. - S.W. - 32.1
14" stump - S.E. - 58.2
Corner as used lies ±18' (by scale) South of ℄ T.H. 30 on Curve.

8-10-82, ¼ Cor 26-35: Dug from Mn/Dot P.I. (disc in concrete) found on South shoulder T.H. 30 appx 18' South & West 5', East 3', and South 9' by 8' deep to clay. Old road down appx 6' and good black dirt but there was a pile of

Timber and lime rock in the blank dirt across the East ½ of hole. Found nothing. The line of the fence South is 1½' West of the P.I. and the ℄ of the road Nath is 15' East of the P.I.

Must dig North to edge of blacktop and East to thoroughly cover center of old road and doubling ½ Sts

See P.C. File (R13W) for old road plat in area of conn.

5-12-93 Accepted location of T.H. 30 P.I on final conn location. The PI falls on line From the S¼ Cor 35 over the N-S Fence @ the Center 35 and also on the line from the N¼ Cor 26 over the N-S Fence at the Center 26. It is also in line with the fence running South and the ℄ of T.H. 30 running East. The T.H. 30 R/W Maps indicate the W on the center of the E-W road here. (See Dwg 5-1A)

Gov't Notes M.G. Kinnick 1954 1/4 corner 36 & 35
40.00 set temp section post #532604 (2)
West on true line between sect 36 & 35
40.00 set 1/4 section post. V 10° 30'
Mound with trench pits and charcoal
stake and Osage Orange set's
N.E. & S.W.