7-4-1965 set C/M one ½" x 2' rod. (1)
10/17/91 set 1" Type/cap 2" in Blacktop

¼ Corner west ¼ 30 Pleas. Grove 105-13

east ¼ 25 High Forest 105-14.

#533006

No records —

1965 J Kerr run line SW corner 31 to west ¼ 19. on established long time corners on Twsp. line. Set C/M at ½ the distance from west ¼ 30 to west ¼ 19; this being equal & straight by original govt records accepting the corner at West ¼ 31 set by Minn Hwy Dept as it lays. each half mile of this two miles 2631.3.

over RPS.

Cove Rd —
No. on So. pass ... pool
Block 6 S 22 = W55
Block 6 S 23 E 165

Rec	tile pole.	SW.	40.5.
"	power pole.	NW	57.3.
"	power pole.	NE	59.3.

corner lies on center of road running north & south.
corner lies 3' north of the south edge of swale
running east and west.

6/2/89 DUG WITH BACKHOE TO COVER E INT OF RDS N-S-E-W DUG FROM 6' NO. OF C.I.M. TO 16' NORTH & 4' EAST & WEST OF C.I.M. 6½' DEEP TO CLAY (FO NOTHING) AT 5' DEEP THERE WAS AN OLD ROAD & AT 5½' THERE WAS ANOTHER OLD ROAD ON A 2" LAYER OF BLACK DIRT, ALL OF THIS WAS VERY HARD DIGGING. NO SIGN OF ANYTHING BUT TWO BOULDERS IN SUB SOIL

1/4 CORNER W1/4 30 PR GROVE 105-13 (2)
E1/4 25 HIGH FOREST 105-14

6/1/89 County Surveyor set 1/2" iron as R.P.
on line to P.K. nail in face of P.P. # 47502
WNW OF CIM at corner
#533006

AZ RP iron
4 FT FOUL to W1/4 30 3° 48' 09"

To W1/4 30 (CIM)
VA 0°25'23"
SD 158.75 HD 158.75

10/17/91 County surveyor set 1" Sq pipe/cap in E N-S blacktop C.R. #20. The corner is 11' So. of E twp rds running E-W RP CSD in PP NE 70.23