6-21-1966 set C I M on place Mc Ghie 5/8" rod. (1)

#540209

1/4 corner Center 2 Hi 7 Forest 105-14.

5-1876 Hunter P 294 No 289 L 2. Chas Carrol E Mountain corrected corner set P 193 after finding E 1/4 2

blazed lines for fencing west & north of Center 2 to 1/4 corners for fencing corner post considered as now true corner. later

---

11-1887 Hunter. P 423 No 412 L 2 John Griffin found corner standing as set P 294. tested stake by witness trees. also checked meas south to be same as P 294 — south 15.43 to property corner set by deed then 23.93 to S 1/4 2. — 16 west set prop corner M & L. 20.08. also See R Fraser field book #10 P 16

.1950s Skerl used corner post as corner

Mc Ghie set 5/8" rod just west of post leaning east as corner.

Cover

6-1966 J Kerr. an extensive work by McGhee done from rod and corner post proven as corner as near as possible set C/M in place of rod.
had to dig post out and move it east straightening up post at 10" white or hard oak post.

- 16 west set 120 D as 1/16 corner N & L 1325.16.
this 120 D lies a little north of being under new E-W fence. 20'± west of west RW fence u.d. 63. R 1325.28.

1951 J Kerr B52 P25 run line south to 2 1/4 2596.03 set 1/16 pipe N & L. (used 1968) Record 1887. 2597.76.
Corner 1/2" pipe inside of 1" pipe
PP NW 86.22' - 12" oak SW 44.6'
20" Burr oak SSE 46.8' east of center line 2. 10± N & E W fence.
there is a rod at 1/16 corner, there is no fence N or S. - McGhee and Sanborne.

1/4 CORNER CENTER 2 HIGH FOREST (2)

#540209 105-14

9/18/89 FD CIM SET IN CONC. AT SURFACE
± 1.0 NE OF C.P. TO FENCES E-W-S

7/24/03 Robert Fraser (pg 712, No. 625½) Found and used corner post which Mr Fulton said he put in place of stake, that in cutting down tree the stake was broke off. chained west 20.08 set ½th stake w ; L