1 11-6-73 set nail on sec line on random meas ①
4-19-74 set a 2 in. cap over a ½" x 2' rod #540706
1/4 Corner West 1/4 7 High Forest 10 5-14
East 1/4 12 Rock Dell 10 5-15

4-1872 Hunter P194 No 205 S 7. J Donnelson, M Olson
found stake standing in grove, tested B trees, found corner
-16 N. set stake M & L. 1990' N 1°10' E (1313.4 (2626.8
- meas south 39.66 (2617.56 N 52° E.
Corner not midway not on line
16 N lies 19.35 west 1/16 E to which is center N W 1/4 7 (1277.1
then 19.77 (1304.82 to 1/16 stake on N-S 1/4 line

9-1913 D Williams P 228 B S 12. J Hanson C Bochm.
found limestone at N W 7 - ran & meas 2 miles south (no

to boulder stone in road at W 18-19.
- set 1/4 post as corner with 2 witness trees.
8" B. oak NE 37.5 – 9" Black LE 3.6
- each 1/2 mile 26.34.
- corner in east road ditch, 1.0L north of fence west

Corner in long controversy as line and meas Varies.
example R Hunter 4-1872 p144 5244.36
Dave Williams 9-1913 p228 B 5268.0
final D Williams corn to C/M W6-7 5254.51 11-5-73.
Hunter gave no hint as to directness of line and comp.
meas indicates some kink but using Williams corner
direct line as W 1/4 7 comes near recorded meas east N 1/2

Card # 2. West ¼ 7 High Point 105-14. #5407046 (2)
East ¼ 12 Rock Dell 105-15

6-15-73 Meas random rail center enters roads at
21¼ 7-18 North. 2618.64 (+4.75) 2623.39 to W¼ 7 rail.
then north. 2631.39 to C/M at W 6-7. 5254.78.

11-5-73 Meas. direct line from riser over D Williams
iron found. 10-3-73. To rail set on direct section
line in line fence west at W¼ 7. 2623.94.
- Rail at W¼ 7 to rail in line fence east at 1/16 N 1318.45
- rail at 1/16 North to C/M at west 6-7 1312.12
2630.57

Record E½ 2617.56 N½ M&L 1313.4 (2626.8

W¼ 7 Rail should move 1.3' north final would be S-2625.24

1/16 rail move 2.51 South N 1314.63 M.&L. (over.

Meas from nail at W 1/4 T east to wire of N-S fence at ac
rear on N-S of 1/4 line 1278.73 from true direct line.
no actual record would compute to. 1277.76 from north.
Meas from nail at 1/16 north of W 1/4 T east to wire of fence 20'
S of corner post 1280.58 R 1277.1 but on digging
extensively in 1971 a stake set in pile of stones 4' west
of corner post from stake found believed could be corner.
or 1276.58± result corner W 1/4 T & 1/16 north should
be set on direct section line with iron at W 7-18 accepted
as true corner - evidently not Hunter corner (lost).
RP nail at W 1/4 T. 53.25 N W to punch hub & end 12" drive Cubs.
61.53 W to conc nail N side corner post.
RP nail at 1/16 north 35.14 E to conc nail top corner post.
63.7 N W to N edge No plate # 7201 E side RP.

Card 3 West 1/4 Cor 7 High Forest 105-14 #540706 (3)
East 1/4 cor 12 Rock Dell 105-15

4-19-1979
Set C.I.M. over a 1/2" x 2' rod
Corner falls on the East edge of the road.

R.P.'s

Co. Surv. disc P.P.# 42680	N.W.	114.2'
Conc. mon/ Cor. post	W.	61.95
Punch hole S. end driveway CMP	N.W.	53.9.

1/16 North
Set 120 penny spike.

Co. Surv. disc. P.P. 7201	NW	- 66.57
Property Cor. (3/4" rod)	E.	- 34.57

Fall, 1982, W1/4 Cor 7: Found CIM OK and shot corner.
See Drwg 5-17.

Cand 7-8-17-18 Sage Stn
Fd, stake set

11-10-82, Center NW 1/4 : Found rocks where stake found in 1970. Removed rocks and dug down finding only remaining 4" of stake (down 1') Shot from traverse pt. Left spike only at surface. Center .7 South of E-W fence and 4' West of corner post to fence South; however, limit well with fence further South.

Note: Cand 7-8-17-18 @ Center NW 1/4, 1970: Fd likely stone 4' ± West of new corner post, set stake (limb of tree) in many stones and glass found near stone Fd