1

#541205 (1)

section corner 11-12-13-14 Hi Forest 105-14

11-1907 C Armstrong P110 B J Kelly, R Thomas & others

assumed unmarked corner

split distance between rows of cottonwoods 101 links.

true rows likely running east & west

Cottonwoods completely gone — corner lost

see Kerr BK 28 P. 36 also Kerr 1948 Bk 38, P. 11

9-1924 Co H D B43 P2. likely assumed corner.

P I set Sta 68+32.7 Δ 90° 39' right from north

show Hunters holes. 2677 east to 1/4 12-13.

then 2677 east to town line. E 12-13.

Meas north P I to 1/4 11-12 2629.1

RPS PI Poplar 2E 59.2 - C wood NE 55.1

(over)

Station at 1-2-11-12 stone 15+78.3 or 5254.4.
" " 11-12-13-14 PI 68+32.7.

Record P110 B. M&L 2627.13 or 5254.26

9-8-71 Co surv. set nail in center Turnrode on transit line from CIM over org stones at 10-11-14-15 and rod set at ¼ 11-14 on line of county nail found and set .95' E of this nail which is exact line from 1/16 iron north of center 11 10-5-14 projected carefully south. to this point .95E nail and 2681.15 east of CIM at SW 11. This nail came at 2680.82 and should be .33' further east to be M&L as survey shows.
- meas north 5247.7 to CIM over stone & iron R 5252.28
- meas North to point in line fence W and E road (would go west 3.1' to be on direct line and 14.92 north to be midway) 2608.93 R 2626.14 act midway 2623.185

J. K... 1948 Book 38 P.11 - used Something as Corner

#541205 (2)

Card # 2 11-12-13-14 High Forest 10 S-14
did not dig for corner here or 1/4 11-12. as records
indefinate as to what set of anything. Center 11 - W 1/4 11
and SW 11 found as quoted in survey but 80 1/16 east of center.
a point, 33' east of nail set as 11-12-13-14 may as
well be accepted as true corner until proven otherwise.
RP nail as set 92.0 E.S.E. To center E side PP # 9648.
97.93 ENE To punch mark on clamp below bell.
No permanent corner set or searched for. (very poor records.

11-18-1975 Dug with backhoe in "T" intersection.
Found nail 1.2 E and .2 N of 9-71 traverse nail
Found 120d nail and wood hub 1.7 S and 1.4 W of traverse nail
Found post stub with two wood hubs and 120d nail
in original soil 2½' deep 6.1 E and 1.8 S of traverse nail

Set 3/4" x 18" pipe to hold location of post, tube, and 120d nail. Pipe 6' E & road N and 1½' S & E-W road

RPs CSD N side sawed off pole with telephone box NE 92.70

CSD in pp # 9648 SE 85.68

— Corner not Found —

Cor's Notes 4 to by 1853

80.00 set post to corner for sect. 11-12-13-14 in mound of earth & sod deposited charcoal made trench, pits & planted Osage Orange seed W W & S E.

5-1948 Kerr BE 38 p. 11
Survey in NE Cor. Sec. 14