X 11-10-82 - Set ½" rod

#541605

section corner 16-17-20-21 Ht Forest 105-14

6-1872 Hunter P207 No 215 S16 Rangue J Rehilley & others used corner post of fence claimed as true corner.

-16 east set stake M & L. 19.89½ (1313.07' S 89°25'E

-16 north " " " 19.90½ (1313.73' N 1°30' E

-16 center SW¼ 16. set stake inters lines.

Minn Hwy Const notes. M.H.D.

Sta 420 + 92.9 or ~~2603.2~~ 2617.0 R.B. west to iron pin ¼ 17-20.

accepted corner post as section corner.

& highway built to center above corner.

corner would like fence north & south.

Corner witness Tree by 1853
80.00 Set 1" rebar post to reference for rebar,
16-17-20-21 in mound of trench & pits
planted Osage orange NW & SE

10-20-1982, Sec. Cor. 16-17-20-21: Dug 1 backhoe bucket width centered over a point @ double the line and measure from Sec. Corner 20-21-28-29 over 1/4 Cor 20-21 which came .69 East and 2.89 North of P.K. Fd. @ road surface in ℄ and in line with fence. There was 4½' of fill on clay subsoil. No chance for corner.

11-10-82, Sec. Cor. 16-17-20-21: Set a ½" re-rod at road surface as corner at double the line and measure from Sec. Cor. 20-21-28-29 over 1/4 Cor 20-21. Corner 2.89 North and .69 East of PK shot tag as traverse point. Corner 2.9 N. & T.H. 30 and in line with fence N & S (actually 11° E & So)
RP's: CSD SE side pipe #25024 SNE 116.96 {cone. nail NNE 2.84}
CSD W side wood post SSE 78.20 {cone. nail E 4.78}