X ~~6-1968 set 1/2" iron by line and meas from sec'l and MHD corner noted.~~ 11-8-82 CIR #541705 (1)

section corner 17-18-19-20 Hi Forest 105-14.
5-1870 Perry by Hunter P177 no 188 S 20 C William S. Rogers
found stake standing in road. -
tested by stumps of B trees - found correct.
- meas south 40.15 to stake in mound in line fence east.
≥2649.9

10-1888 Hunter P425 no 414 S 19-30 R Sage & Hulbert.
found stump NE BT - NW tree gone. - found small
piece of old stake remains set 2 foot quarry stone
in its place.
-16 west set stake N 0 L 20.01 1320.66
-16 south set stake & stone N 0 L 20.15 1/2 ~~1329.9~~ = 1330.23
-16 center NE 1/4 19. set stake N 0 L 19.99 1/2 on E-W 1/16 line.
1318.35

(over)

School Dist Add No 98 Deed book no 49 page 632
12-20-1878 Hiram & Ellen Salmon lies in extreme SW cor 17
10 rods N & S 165' (132') 8 rods E & W ½ acre. to hold forever.

Minn Hwy Dept. const notes
Sta 368+39.5 or 2640.6 west to sta at ¼ 18-19
assumed. ~~Loop road south~~ (no stone) 1888 record. 2641.32.
~~No - Int line to N-Rd So 6' right~~
PI sta 365+89.9 long 358.4 PT 369+48.2.
℄ hwy as const lies south of assumed sec cor. ℄ old road.

6-1968 J Kerr dug for corner in old school drive but evidently graded out when drive rebuilt. corner gone.
- meas south to stone found 5326.5 record 5332.14.
used line from ⅝ E19. other point 2636.7 east of fence corner of ½ north of center 19. set ½" rod on this projected line 41' north of ℄ state road. or 35' south of E-W school fence. 6' east of school fence north. - 59' north to center 20" burr oak - line south 8' east of tree - West edge school drive. Meas south to fence west 1328.83.
record 1330.23.

Albany, West 15' MND Topo

Card # 2. 17-18-19-20 High Forest 105-14 (2)
1973 found rod set by J Kerk 6-1868 dug
enough to know old Corner would be gone. #541705
- rough meas line from west on S side Hwy 30
- iron close to 165' to old school fence south of building.
one old school. => must mean Note
- Meas S Electronicly See map 1/4 19-20.

Cor' N-15 Gr. by 1553
80.00 S-E post to corner to set 17-18-19-20
Bur Oak 10 in N 44 W. 55 lks
Bur Oak 12 in N 2 E 255 lks

11-3-82, Sec. Corner 17-18-19-20: Dug two bucket width with backhoe centered 3' East of Kerk iron. Found area had been cut to clay 5' deep, even Prelow bottom of ditch here.

See Vertical File - Survey Data Range 14 For Mn/Dot Topo here

11-8-82, Sec. Cor. 17-18-19-20: Set a CIM over a 5/8" re-rod as corner 3.80 E. and .19 N. of Kerr's 1/2" rod (drive down) Corner set at T. Hunter's full measure (Survey No 414) from the stone found at 1/4 Cor 18-19 and at T. Hunter's prorated measure from the E-W 1/4 line Sec. 19 (prorated against Hunter's measure from the SE Cor 19 to the E-W 1/4 line Sec. 19 as per Survey No 414) Corner appx 42 1/2' North of ℄ T.H. 30 and on W. edge of driveway and 6' E of ℄ road South and 1/2' East of West edge of cattle guard in driveway.

RP's:

C.S. Disc in pp 7131 SSW 127.64
South edge cone. cattle guard in driveway North 4.28