X 11-30-72 found boulder with + set iron rivet.

#542804 (1)

¼ corner 20 - 29 Ft Forest 105-14.

5-1870 Perry by Hunter R 177 Ro 188 & 20 C Wilcox, J Rogers.
"Quote" - Sluice built over this stake, the center of which is
said by Mr Rogers who helped build it to be exactly over
the orig mound & ¼ post.

- Meas west 39.81 S 89°10'E 2627.46-
- Meas east 39.86 S 89°25'E 2630.76
- 16 north set prop corner M & L 20.20 N 25'E

---

1959 Co Hwy Dept B 202.
found boulder with cross.

over)

| | | | |
|---|---|---|---|
| Spike | tile pole | NW | 34.96. |
| " | power pole | NE | 45.17. |
| " | corner post | E | 33.28 |

Mean south 2630.92 To Center 29.

Mean north 5329 ± To rod in center Hwy 30.

---

11-30-72. dug with air hammer. front deep. found. 2 to 3" Cross on large flat boulder. 3.2' deep. in center road a little south of woven wire fence east.

78.7 NE To Conc nail in knot on NW side power pole # 11433 up 6'

100.0 about 2' N of E to 5/16 x 4' bonnie rod up 2" about 8" N of hy woven wire fence.

Card # 2 1/4 20-29. High Forest 105-14. #542004 (2)
2-1-73 found book with survey of sec 29 105-14
about 7-1-03 by Robt Fraser. page (19) Book # 10
North line section 29 short 34 1/2 lks (22.77'
Corner boulder with cross not mentioned but used to set
corners of SE 1/4 of NW 1/4 29. - used stone at center 29
found. Could have set boulder found. as set 1/16 east
for line south. also set 1/16 property Corner S for line W.
"F B" came west 3 1/2 lks and short 16 1/2 lks 6.93'
If center 29 stone found (Must hammer like this arrow) Corner
found Can be proven. Check line occupation fence 1/16 South.

9-22-82, 1/4 Cor 22-29: Found a RR spike under new blacktop
mat. Checked against 1972 RP's: Conc. nail in knot on NW side
PP # 11433 NE 78.69; small iron (top foot bent over and fence
now gone) E 100.00. Removed RR spike and dug down to
1972 iron (down 6"). Iron a 5/8" re-rod and was .06 N.

Govt Mons Yu by 1853
40.00 set temp 1/4 cor post
West on true line between cor 20 & 29
39.95 Set a 1/4 cor post in W. 7 50'E
mound of earth & set. Dug pits around
made trench & pits, planted Osage
Orange seeds N & S

---

and .09 E. of the RR spike. Set a CIM over the 5/8" rod on the corner. Corner in ℄ C.R. 8.
RP. Concrete nail in knot on NW side pp# 11433
NE 78.65