3-21-73 set 30" x 3/4" □ lead bndy bolt-true N&L 2651.77
cert to be made & recorded 4-73. ①

1/4 corner 22-27 Hi Forest 105-14.
#542264

6-1899 H Fraser P659 No 587 S26 Iron Board.
Could find no corner, all settlers agreed corner stood in line fence running west. As corner gone set stone corner on line fence west & mid bng 40.18 (2651.88' on section line.

12-1910 Ch Larson P146 B S27 John Fitzpatrick
found stone boulder
run line to S 1/4 27 (point set from witness tree) did not look for stone found 1905 by Armstrong.

over)

set stakes on N-S ¼ line at 660' and 1980' for property boundaries east.

3-21-73. found PK used by MHD 2' west of west edge of S bound concrete lane Hwy 63.
Ran careful electronic traverse from NE corner 27 to center old post hole in clay found at NW corner 27 (½" rod)
- found computed meas at 5303.54 or 2651.77 midway
- will of record 2651.88
- set ¾" x 20" □ head bridge bolt as corner. M & L 2651.77 which lines fence west and PK found.
- corner 16.75 due west of MHD PK. 18.75 from Conc.
95.85 SW to center no plate PP# 11001 direct meas
148.53 NNW to top center S edge S end 24" farm drive C.

#542204 (2)

High Forest ¼ corner 22-27
Govt Notes 4" sq by 1553
40.00 Set Iron ¼ sect post
West on true line between sect. 22+27
40.12½ Set a ¼ sect. post on V 7°28'E
Mound of earth & sod deposited
Charcoal made trench & pits, planted
Osage Orange seeds N+S

3-28-97 CGC says no monument @ N¼ 27 & Con 27
Call MNDOT but they have no ties.