1 3-21-73 set 1/2" rod in old post hole - proven corner
10/12/88 SET TELSPAR/C.L.C. OVER 1/2" ROD (1)

section corner 21-22-27-28 Hi Forest 105-14
#542205
6-1899 H Fraser P659 no 587 & 26 Town Board.
found old stake on east side of fence corner post.
set stone in place of stake.
- meas east 40.18 to stone set midway & on
line fence west as agreed by settlers.
7-1902 R Fraser old fieldbook #10 P54 & 27 Hiser.
Corners "C" and "D" used previous survey no desc.
- Sec 28 Page 55 as "A" found square stake at Corner
post of fence, put stones arround.
- meas west short 15 1/2 L. 10.23' or 2629.77
above 1/16 south as "2" line & overran. 8 1/2 L. 5.61/one

or 2645.61 M&L 1322.8
3-19-73 ran and meas line from C1M at 1/4 27-28 N.
found vertical boulder 1' SE & RR tie corner post at 1/16 not
position of corner. meas 1325.6
- cont line N on 50' offset east 1323.06. to line of fence west.
50' offset fell 3' east of fence. south.
- found 10" dia dark hole in clay at 1325.86 ± in line fence,
at about 53' offset. 23.92 N to nail W side 14" oak.
RPS 60D center hole 16" deep 36.60 N to nail N side 16" oak.
3-21 meas elect. from 22-23-26-27 on traverse to above.
meas 5303.54 record 5303.76 will 4 reset.
accepted dark hole (extends 18" into clear clay) as corner
set 1/2" rod driven thru hub cap in case lead was pulled.
- set 1/4 22-27 M&L 2651.77
- meas south 2650.45 with stone found. 1324.85 N 1325.6 S
1/16 stone not on line being 1 1/2' or so too far east and some .4 too far north.

#542205 (2)

SECTION CORNER 21-22-27-28 HIGH FOREST

10/12/88 FOUND 1/2" ROD, CHECKED 105-14

TIES 23.88' N TO NAIL IN WEST SIDE OAK

36.61 WEST TO NAIL IN NORTH SIDE OF OAK

SET TELSPAR/C.I.C. OVER 1/2" ROD

High Forest Section corner 21-22-27-28 3
Govt Mons Yr. by 1853 #542205
80.00 Set post - corner to Sec 21-22-27-28
Bur Oak 12 in N 55 E 125 lks
made track