1 10-19-73 set C/M over 1½"x18" pointed bar and stone. (1)
Corr 3-14-75 #542705
section corner 27-28-33-34 Ht Forest 105-14
10-1905 C Armstrong P94 B S33 F McCall, Stewart.
found stone. tested from east by running line over 1/16 cor
and 1/4 27-34. (B tree - N 47° 10' E 64 lks. to 1/4 27-34)
- meas west 2634.2 to 1/4 28-33
- set property corner 362.28' east of 1/4 28-33 as located
-16 south set iron bolt 1317.5 M&L.

10-1905 C Armstrong P96 B NW 1/4 S34. McCall.
found limestone
-16 east cedar stake M&L 1325.75. (see N 1/4 34)
-16 south stake " 1317.5.

Co H D B 321 1966. line from. 1/4 29-32 east to 27-28-33-34.

2655.42 • 2634.25 • 2629.27 • 1329.03 • 1329.3 □

~~R 2639.12~~ P491
2652.32
R P388
80.40 mls Gov't
5306.4 - 2 2/3 lks

R 2634.20 corn 94B.
R 2635.82
P491

2634.25 corn 94B

1325.75 1325.75 corn. P96B

79.90 Gov't

set 3/4" rod by line & meas from 1/4 27-34 over 1/16 west 1329.03 then 1329.3.

1/4 P P SE 71-89 — 1/4 P TP NE 60.88
1/4 P F P NW 59.46 - Hube N 50.95 - NW 57.8 - NE 58.61

P 491 did not explain that Δ line 29 — 80.40-Shows 79.90

1/4 29-32 west to P I 2659.67 by road plan prints.
Hunter total mls 80.40 - 2 2/3 lks. 5304.64

Note: Co. H.D. - 3/4 rod - Should move ± 5' East

Card # 2. 27-28-33-34 Hi Forest 105-14 (2)
#542705

10-8-1973. found iron bolt set as 1/16 corner south by Chas Armstrong 10-1904 Page 94 book B. M & L P317.5. - ran traverse from 8" □ 2 stone at 1/4 33-34 in Flemerville village around lake and Hwy 63 and Co R #8. computed distance to iron found at 1316.33 from stone to iron, as no positive section corner found. could now re-set. No RPs to iron found blazed tree within 5'±

10-19-73 dug with air hammer and back hoe. found limestone 2"+ thick 5" top 14" bottom 18"+ long leaning easterly with 1½"x18" pointed iron shaft by stone. set iron as riser with C/M over all. stone set vertical in

spot plainly shown as where stone sat.
Meas final South to 1/16 iron found. 1316.53
Meas final then to Latons at 1/4 33-34 by traverse 1316.33
1/16 iron lies .10 S. .40 E of true N & L.

RPS. 59.02 NE to Co disc WNW rede tele cable pole. tall.
69.03 SE to Co disc WSW rede PP# 10913.
40.7 SSEly to punch mark in Top Cable clamp lug End
46.18 SW. ly to same west end (cracked lug a little).
Corner center road. 1.76 east .54 north to traverse nail

High Forest Section corner 27-28-33-34
#542705
Coal Notes Yr. by 1853
80.00 Set post-cor for sect 27-28-33-34
Bur Oak 12 in N 35 W 350 lks
Bur Oak 12 in S 9 E 60 lks " "
Made tracks

7-1-96 FOUND CIM IN GOOD CONDITION. SET REF PIPE W/CAP IN NE SEC 33 SW OF COR.
TI@ REF PIPE
ZRT P.K. IN PP # 2898 (12" POLE WEST OF COR ON SOUTH SIDE CR 35)
TO SEC COR 147° 27' 12"
TO SES COR 27-28-33-34 HOR 112.27

REMOVED CIM
7-8-96

10-25-96 CHO SET 1" SQ PIPE W/CAP