1 6-14-1971 set C/M over long sash weight. #513004 (1)
Inters. Links 2

¼ corner 30-31 Hi Forest 105-14.
4-1884 Hunter P388 No 379 L31. 21E Mayo.
Corner in marshy road const. area. Mr A Munson avers it stood 5 feet east of west ditch in line with small tree which pronged within one foot one mear N line 31.
- set corner on line & gont perp - NW cor 31 assumed as fence line
- east 39.85 (2630.1'
- west 39.45 (2603.7'

10-1888 Hunter P425 No 414 L19-30 R Sage W Hulbert
At SW30 (NW31) found stake close together in road on line brush fence east. Claimed by A Munson as orig corner. ~~as NW cor 31 there~~
- set boulder stone with old stake by side - as ¼ 30-31 Missing cor

run section line and found stake set 40 chains from NE cor 31 in survey P 388 ~
- set stake at 39.85 = 2630.1' with stone by side as N 1/4 31.
would likely come in west ditch as in P 388.

12-1915 J Kerr P 242 B 231 Attorney for Brin Estate
dedist found corner - run line from Center 30 south
to S 1/4 31. 7903.44 - set Center 31 at 1/3 distance
did not set N 1/4 31.
Prorated Meas Center 30 south 39.98 W 3987 E 39.92 1/2 2635.05
Johns prorated 1/2 mile 2639.48'

5-13-71. ran aerial line from 5' south of 1/2" iron found at W 30-31 set by joint crews crew & Troad. To latch as near in line iron set for C P I on W edge road. set 1x2 hube on this line on opposite side of road. - later enters this line by line from Center 30 area. or line 4 fog post at 1/4 19-30 over old post stub at 1/16 with drone short 1/2" rod which came a couple feet from W. edge road at 1/4 30-31.

#543004

(2)

Card 1/4 30-31 High Forest 105-14

#2

McElhiney crew meas from rod found at W 30-31 east and tied up with nail at 2480' - found it took 103.85 to reach rod set at inters lines described. 2593.85 39.30 chs. R 2603.7

- Summary meas of S line 30.

Hunter 4-1884 p388. east 39.85 (2630.1) west 39.45 (2603.7. 5-9-73 elect

Hunter 10-1888. p425 east 39.85 (2630. (comp meas E 2626.33

govt meas N side W½ S30	39.80	Hunter 1888	39.64
govt meas S side W½ S 30.	39.60	Hunter 1884.	39.45 sum error
govt meas meas E-W 1/4 line W½ 30	39.70	Hunter 1888	39.41

6-9-71. found center 30 stone. which came 1.42' east of random N-S 1/4 line tied down as chart ½" rod between tube. (over)

Corner now will go 2.84 east but appears rod at W 30-31. would not be 5' south, only about 2.27' south (will dig)
- recorded meas west of 39.45 (2603.7 far from correct.
McElhiney meas of 2593.85 corrected rod to rod west would have added 2.84 + 3.01 or 2599.7 or 4.0' short of record.

6-14-71 Co surv. after finding center 30, SW 30 and setting SE 30 set ½ 30 31 where lines intersect.
- set long rack weight below C/M.
- corner 4.5' east of west edge traveled road. Meas west to Stone at W 30-31 2599.85 ± Record 2603.7
" 6' west of center " "
- NW corner of E Culv headwall. SSE 245.9
- Center number plate # 10786 PP SSE 142.1
- N-S fence on east edge road E 39.7
angle direct west to north 90° 31' See Center for Meas 5-9-73.

High forest 1/4 corner 30-31 #543004 13

Govt Notes Yr. by 1853

40.00 Set temp 1/4 set post

Course W 89°49' E on true line between

Sects 30 & 31

39.60 Set 1/4 set post in mound of turf & sod, depressed charcoal, made trench & pits. planted Osage Orange seeds NWS

Fall, 1982, 1/4 Cor 30-31: Found and shot CIM. See DRWG 5-17.