/ 6-9-71 found stone, set rod at temp cor. #543009 (1)

1/4 corner Center 30 Th Forest 105-143.

10-1888 Hunter P425 No 414 & 19-30 R Sage, N Hulbert set boulder stone at inters lines also boulder one rod west as witness corner

-16 West established corner on line N 89°55' W.

at 19.85½ then 19.55½ to W 1/4 30. (a stake & stone set M&L.

1310.43 1290.63

govt record - 39.70 actual 39.41

bearing 1/4 line north — N 2 3/4° E.

stated line for fencing from 1/16 west-north-

6-1892 Thos Fraser - P480 No 457 & 30 John Logan & others.

found boulder. planted by Hunter P425

-16 north set boulder stone M & L 19.96 ft. (1317.94'

-16 west found stone corner set by Hunter P425 no Mon.

12-1915 J Kerr P 242 B L 31 att. for Brin Estate.
found corner easily no description.
Meas south 1½ miles 7903.44'
Could not find N¼ 31.

6-1968 J Kerr. for east line 19 & 30.
Meas east from fence running north.
Mean of meas N line 39.84 & L line 39.85. - 39.84½ (2629.8)
on meas east fence N got 2630 to direct line PI at L E30
and C/M NE 30. assumed point 4.8' E as corner which
would be close of 2630 from ℄ road L at center 30.
Common land north side center 30.

9-1924 B 39 P80 Co HD. found stone
RP & F.P. SW 66.9. - Lp tel pole SW 44.0
Lp in stump SW 84.2

Card #2 Center 30 High Forest 105-14. #543009 (2)

5-10-1971 Co surv. used Center East-west road as 00 meas north
well west of brushy farm building shelter area in line brace post.
- drove small hard nail on east side brace post as sta 43.0'
- found center corner post (hard nail W side post) at 1316.05. R 1317.94'
- dug out all stones in area found most Sandrock type in old concrete
around post 2 larger boulders may in 1892 been set placed as corner.
- found 4" diam corner post of fences S & E at 1/4 19-30 (huge
concrete based for post and brace terminals at 2632.5' R 2635.88
- Pro rated record for meas south to 1/4 30-31.
West 39.98 (2638.68' East side 39.87 2631.42 - 5270.1
Mean meas 2635.05 , Johns 1/3 Center 30 south to S 1/4 31. 2634.48

5-13-71. used E line 8' west large post at 1/4 19-30 (proven OK)
and point 1 foot or so west of corner post at 1/16. south. and pushed line
south to Center road on 8' E. which came corrected back (over

2.24 east of .00 nail going west. pushed line S to S 1/4 30 area.

6-8-71 dug with back hoe for stone, found tele cable & broke it. almost directly over corner stone found. with piece of steel fence post, 120 D nail and other iron and wood hub stake. set bearing rod 5/8 or 3/4 x 20" as temp corner over stone with piece of fence post on north side corner stone.

- Corner 3.65 east of .00 on lot fence running north. other RPS later. Meas now west to stone found 2605.77 R 2601.06.

- line pushed south as random N-S 1/4 line must now be considered as 1.42 east at center or 2.84 east at S 1/4 30.

- Meas north stone to metal 4" cor post 2633.97 R 2635.88

N to E-W fence. 1317.52 - fence to 1/4 29-30 1316.45

Card # 3 Center 30 High Forest 105-14 (3)

#543009

6-1[illegible]71 referenced corner.

- Lead nail on east side white cedar Cor P & fc W 4'W & N 44.82.
- Center Tele bell on iron post NE 91.0.
- center tele bell on iron post badly bent North SW 42.9.
- 20 D in top corner post fence E & S SE 45.55

Corner in center road south at N end of road or little east.

Corner in center east-west roade.

Fall, 1982, Center 30: Found and shot iron.
See DRWG 5-17.