#551004

/

1/4 corner 10 - 15 Rock Dell 105 - 15

11-1857 John Fellows P42 No 64 L10

used corner -
set 1/16 east 19.89 M&L - 1/16 west 19.89 M&L blazed.
set 1/16 north with B.T. Mason south half (see book faint
(corner would have to be set midway or M&L) without
much error if any.)

Set by Michael Karrick 5-1854
40.00 Set quarter section post in mound with trench, pits and charred stake and Osage Orange seeds NE & SW

12-1984 Vince Fangman set RR spike M&L (2637.47) as 1/4 Cor For 1/4 line North. Says position fits middle of E-W road, fits a projected fence from the North (1/4 mile away) and is about 5' east of a projected lane fence

that starts ± 600' South of 1/4 corner
RP's: P.K. in Power pole SSW 31.69 (W face up 5')
8d nail in 8" mulberry SW 47.11
PK in corner post SE 84.45
Measured S273.10 to N1/4 10.
(1984)

9/30/88 FOUND R.R. SPIKE SET BY VINCE FANGMAN
CHECKED RP's 8D NAIL IN 10" MULBERRY SW 47.13'
PK IN PP TREE GREW ON LINE
84.7' SLOPE CHAIN TO PK IN CORNER POST S.E.

6-24-93 Found V. Fangman Railroad spike Referenced & dug out. Set CIM over 1/2" Iron at R.R. Spike location the corner falls in @ E-W Twp Rd R.P's P.K. Nail w/ribbon in West Face P.P. #6901 SSW 31.39'