1-26-78 Set C.I.M. over a ½" rod M+L by the Traverse at 2643.76

#551204 (1)

¼ Corner 12-13 Rock Dell 105-15

3-1858 John Fellowe P51 No 74 L13

used corner. E 40.24 2655.84 W 39.82 2628.12
S 39.80

~~1/16 east M&L 19.98~~ L88 E
~~1/16 west M&L 19.96~~ L88 3/4° E } 1/4 13-24.

indicates corner not midway or on line.

9-1913 D Williams P228B L12. T Hanson, C Borhm could find no evidence of knowledge of corner so set point M & L to center crossroads west at L W 12.
both corner assumed - no regard to records, very scant as they were - set corner not described took RPs.
telepole - 61' L63°45'E.
Twin oak 12" each - 69.2' N 58° W. this tree in cattle lane (over)

Corner came in center east-west road.

10-2-73. Meas elect & line from nail at 11-12-13-14 R Dell east - nail at ℄ road in line fence N 2647.71 to cor.
- Meas in 6-73 from nail east to random nail at E 12-13 R Dell - 7-18 Hi For. 2624.95 total 5272.66 R 5280
line fell .34 ℒ℄ east nail
- dug from 60 7' west ℄ nail to 4' east and 60 8' N 45 road to near bed clay: road slopes up to 300' west as road washed and wore away. set nothing.

4-26-74 Sol C.I.M. M-L by elec. dists. Total mile = 5287.52
E ½ = 2643.76 W ½ = 2643.76

R.P.'s
Co. ~~Surv. disc. west side cor. post~~ N. 35.77
Co Surv. disc. So. side P.P. # 71.56 N.W. 96.5' 96.55' (1986)
Co ~~Surv. disc. N.W. side cor post~~ S.W. ~~44.26~~

#551204 (2)

1/4 Corner
set by Michael Karnick 12-13 Rock Dell 105-15
5-1854
22.45 Creek 4 lks wide runs North
40.00 Set quarter section post
Burr Oak S 58 W 127
" " 7 N 28 W 197

9/27/88 FD CIM IN GOOD COND. 0.25' DOWN IN E-W TWP RD. 3.0' SOUTH OF & TOOK NEW RP 58.32' SW TO BOTTLE CAP IN N.W. SIDE OF CORNER POST, CSO IN SOUTH SIDE PP # 7156 NW 96.55' OTHER RP's GONE