X 10-15-93 set C/M ones. 5/8"x13" iron rod. ~~School corner 88~~
~~Many pieces of broken cast iron from school desks~~ (1)
#551605
section corner 16-17-20-21. Rock Dell 705-15
~~C+T 3-14-75~~ 9/30/91 Set 1" SS Pipe/cap
6-1895 21 Fraser P 579 No 529 & 17 Marcus Twng. etal
no mention of corner in survey. only measurements
shown to corner from north & west.
2638.68 2693.4
- Meas north 39.98 then 39.90 to NE cor 17.
- Meas west 39.88 then 40.12 to NW cor 17.
2632.08 2647.92

Co Hwy Dept Book 262 P5
Concrete monument with ~~cap~~ gone. "broken off".
Disc power pole. NW 84.28.
" tele pole. NE 82.9
(over)

Minn Hwy Dept Const notes.

Station 105+61.5 at ℄ road south or north County road ℄
℄ stab 30. 48.8' south of section line as built.

indicates 2636.3 west to ¼ 17-20

record. 39.88 or. 2632.08

1935 B79 P8 corner not described. Sta 187+97.8
Cross in SW cor school slip NE 84.15 Meas south
Sp in tile pole NE 76.2 5278.9
Stick in hub SE 84.45
Sp in tile pole NW 65.7 North 5280.2

B 262 Meas south 2 miles 10497.92

School # 88 Ole Jackson. 11-3-1880 SW corner ℄ SW¼ B54
10 rode 165' north and south 8 rode 132' east and west P316
12-1937 Book 383 page 167 calls for addition or
10 rode (165' N&S) 16 rode (264') E&W.

Card # 2 16-17-20-21 Rock Dell 105-15. #551605 (2)

10-15-73 dug about 165' south of north boundary fence of old school grounds running east and. 48.8 North of MHD PK nail

- found double wood hubs deep into clay down 3'+. No sign of cone mon as road all cut away. assume hubs to replacement of original County Monument - set 5/8" x 13" iron in place and above hubs with castiron piece and glaze with C/M. over all flush with road surface.

Meas south ± 2632.4 to E-W fence R 2633.4

Meas north see notes on re-run.

Meas west. 2636.86 to drill rod set then 2647.42 to Sec Cor.

a rail road spike set in black top road by line and double meas. from C/M 8 over stones North.
2635.50

134.0 SSW to Conc nail on E side PP 6127
65.9 NW to SW corner metal tele cable post.
142.0 NE to cross on top conc school step near SE corner of step platform
162.1 NE to SE corner main school rock Corner.
49.5 S to MHD P.K. in No 20.

Set by Michael Kerrick 5-1854
61.90 Road bears N.W.
80.00 Set post for corner to sections 16, 17, 20 & 21 Erected mound with trench, pits, charred stake and Orage Orange seeds at each angle.

Section Corner 16-17-20-21 Rock Dell 10S-15E (3)
#551605

12-17-80 Sec. Cr. 16-17-20-21 Dug from a point 4½' West of the CIM, West 3' and North 4' by 3' deep to clay. Old road on clay. Found a possible stake mark 6.3 West and 3.6 North of the CIM but the old road was compacted so hard into clay couldn't tell for sure. Removed CIM

CIM { 1.0E / 1.0S Mark { 5.7 SW / 7.25 SE to CIM / 8.05 SE to E tie no.

January, 1981 County Surveyor set temp point for McGhee (See Drawg 4-62 for detail) .06 N. and 6.4 West of the found CIM location

9/30/91 County Surveyor set 1" sq pipe cap at position determined in 1980 Survey by Co. Surveyor this corner is 5' west of ℄ CR #3 ; 47' north of ℄ TH 30

OVER →

9/30/91 Cont.
RP's
CSD in So. side tele pole stub WNW 60.95'
1985 G.P.S. mon. (Arends) SW 139.78'
+ in steps of town Hall NE 146.96'