1 10-12-93 set C/M over iron and stone 6' dup (1)
cert 3-14-75 #552105

section corner 20-21-28-29 Rock Dell 10 5-15
9-1876 Hunter P 304 no 299 L 29 Marcus Wing.
Nelson Shireman.
Corner could not be found, as not essential to survey
did not relocate corner.

7-1893 W Fraser P 523 no 488 L 28 Frank Roeder.
Corner still gone. Peter Lee.
Meas from LW cor 28 north 7½ miles to ¼ 20-21 Bobal Magnuson.
which fell short 21 lks. then meas another mile to ¼ 16 & 17.
which fell short 35 lks both giving shortage of 7 lks per half mile
or 39.93 (2635.38) – ¼ 16-17 covered by O Jobson as surveyed fence
– meas ¼ 20+29. (a stone P304) to NE 28 short 42 lks (over) east – no corner used.

for 1 1/2 miles or 39.86 per half mile.
set stone 4 x 14 x 20 which came a little west
of road track

5-1896 Hunter P 598 No 543 S 29 H W Buckland.
David Brandt etal.
found stone set P 523 No 488 by Wm Fraser. 13 15.05
1/16 west set oak stake center road N & L 19.92 1/2 to
stone set P 304 - same one Fraser used P 52B yet
Hunter mine 39.85' Fraser 39.86 very close.

1935 B 79 P 6 corner assumed. PT A 0.1' Left long path
Elec Tab P SW 70.7 - Sp 24" maple along NE 54.0 - Sp 24" Conif SE 58.4
Sta 135+18.4 Mens south to iron SE Cor 29 5270.7

Lee Card # 2.

Card # 2. 20-21-28-29 Rock Dell 105-15 (2)

7-27-71 Co surv set nail in center black top in line center of mean centers of roads E & W (different)

Meas west - 1/10 fence running south 1319.8 R 1315.05

set nail at 1/4 20-29 line center road north 2632.

R 2630.1 (8-12-71) #552105

- meas east to stone found. 26 24 15 - R 2630.76
- meas south to nail set at 1/4 28-29 from south. 26 33.0 R- 2635.38 could indicate corner north
- line from east indicates corner could be north 4.1' but NE cor 28 more than W Fraser record north by 7.2'
- Corner could be west up to 5.6' and North 2 to 4' ± but may be even more if NE 28 too far north.

OVER

10-9-73 used air hammer & back hoe, found County nail and conc nail set 7-29-71. dug 6' square 7'+deep centering about 4'N 5'W dug & probed in all directions: didn't find a pebble above sub soil. Lots (18") of nice black dirt part of it road, probed quite hard, used 4' probe. will go south & search starting at 1/4 32-33

10-12-73 dug again after finding stones at 1/4 28-29 and 28-29-32-33 and make line electronicly. searching to center 6.94 west and 1.54 north found h stone 20" long. 4" thick x 5" top 14" bottom down 6' deep to top of stone. set by Jr Fraser 7-1893 by meas N-S E-W stone believed abt 1.6' N of dd nail or ± 2635.3 To 1/4 28-29 originally set N&L 2635.38

card 3

Card # 3. 20- 21- 28- 29. Rock Dell 105-15. (3)
#552105

RPs to C/M

61.0 SE to Conc. nail in old County disc on NE side PP # 6179

51.5 NW to Conc nail in old County disc in PP # 6164.

46.4 SW to cross in top center conc culv flare 3' ± calc.

corner 7' west center County road # 3.

a line was ran from a point 1.54 north of random nail in center road at 20-21-28-29 over 1/4 28-29 and this line fell about 1 foot from 3/4" iron at 21-22-27-28.

these notes last line must be re-run for final data

Set by Michael Karrick 5-1854
80.00 Set post for corner to sections 20, 21, 28 & 29 Erected mound with trench, pits, charred stake and Osage Orange seeds at each angle

552105

7-2-99
MW AE

Sec Cor 20-21-28-29 105-15 Rock Dell
fd CIM 7" deep in Blacktop,
Broke head off after Cold Recycling
will set pipe 10' long

Prop Cor ——— North of 20-21-28-29
found 30d spike 60' west of ℄
CR #3 and in line of prop fence East.
Ref to 30d spike
Bottle Cap in Pt # 53005 WNW 42.00'
Punch Mark in Lug north end 18" CMP
NE 5.85