/ 7-21-71 set CM over orig stone #552406 (1)

1/4 corner 23-24 Rock Dell 105-15

4-1878 Hunter P 334 No 328 S 23 Hans Amundson EC Stehon.

found remains of old stake in mound with one pit plain, rest gone. set stone 6 x 10 x 20 in ground place. Brass south 39.97½ to section stone 4 2638.3

Meas south 40.05½ to stone set in place 2643.63 post in road.

-1/16 west set stake M & L 19.97. 1318.0

plat of S 23 & S 24 Armstrong took stones stone as set at 6x12x24.

4-1878 Hunter P 335 No 329 S 24 Hans Amundsen etal.

found stone as corner P 334.

(over)

1/16 south set temp stake M & L 19.98 3/4.
1/16 east set stake " 20.00.
1/16 center SW 1/4 24 set stake inters lines.
1/16 north set stake M & L 20.02 3/4.
1/16 center NW 1/4 24 set stake inters lines

5-21-71 set nail in center road in line fence west.
meas from point 37.7 Sf center highway 30.
2644.65. R 2643.63 final meas to stone +.35 2645.0

6-17-71 meas from true center 24 west. To nail
2642.77. R 2640. final meas to stone - 2.35 2640.32

7-20-71 meas west stone to iron set as center
final. 2636.95 R 2636.0.

Card #2. 1/4 corner 23-24 Rock Dell 105-15 (2)

7-21-71 dug with tractor, found recorded 6x10x20 boulder. nearer 8x14x23 - had to lower stone set 3/4" x 14½" reinf rod below stone with C/M on top #552406

Corner came 2.35 east and .35 south of nail set

Meas now to 23-24-25-26 2637.75

2641.9 - 3.8 - .35 = 2637.75 R 2638.35

RPs 107.3 NNW to center no plate # 7023 power pole

24.25 E to cone nail S side corner post

65.27 ESE to NW corner garage foundation

152.97 SE to SW corner house "

42.05 SE to ⌀ in N end 15" drive culv

over

10-25-73

elect mease south 263866 R 263866

elect mease north 264393 to RR spike set as corner 2643.93

as to how 1/4 23-24 lies as to line very close to being on direct line easy to check direct

---

Set by Michael Karrick 5-1854

40.00 Set ~~post~~ quarter section post in mound with trench, pits, charred stake and Osage Orange Seeds NE FSW