8-17-71 set C/M over iron pipe found. #553106 (1)

¼ Corner west ¼ 31 Rock Dell 105-15 & D.C.

6-1875 Hunter P284 no 281 S31 3 Holland Brook J. McDonough

Corner could not be found no evidence or knowledge.

est. corner N & L 39.92 $26\ 34\frac{1}{2}$ set marked stake as cor.

-16 north set stake N & L 19.96 N25°W $13\ 17.36$

-16 east computed length to center of W line straight 39.80 actual length 40.10 - 39.80 : 40.10 :: 20 : 20.15

Making mean east 19.95 when 20.15 to center. S88°36'W.

6-1898 W Fraser P633 no 572. S5 & Eichstaat, T Hagan found stake set by Hunter P284 set stone in place 2x7x14.

-16 east found Hunters stake set new stake & stone on line
19.93 (1315.38') then 20.13 (1328.58') N 89°15' W.

-16 north found Hunters stake set new stake & stone
which proved N & L. 19.94 3/4 (1316.54') N 20' E
- meas south 39.89 1/2 (2633.07

-16 Center N W 1/4 31 set stake & stone at inters line"
stake on east edge big boulder stone.

8-9-71 set nail in line fence south and center of reproduced transit line from east slightly south center road.

8-17-71 dug for corner. found 2" pipe down 26" also recorded stone a L stone broke in half in fill after corner dug. could have been lying flat, likely moved in digging operations when 2" pipe was set. (was unaware corner could be so shallow

See Card # 2

Card # 2 West 1/4 31 Rock Dell 105-15. (2)
8-17-71 con't. set C I M on pipe found #553106
pipe .65 west and 1.87 south of point set.
Corner as set 1317.2 west of 1/16 stake found. R 1315.28
then - 1328.18 east to center 31 found. R 1328.58
stone tore out coned have been east 2'± as indicated
accepted corner as is until proven otherwise by line from
township corner SW 31 105-15 to likely 1/16 stone north of W 1/4 31.
R P S. corner 4' south center road as used.
corner in line old fence (very poor) running south.
15.0 S to 1/2" x 3' rod up 2" under poor fence running S.
230.3 W to eyeball line of power poles & hage transl
line running SSW ly (west side east pole of first H-um poles
to center of east pole of 3 poles at P I of power lines.

John Ball 10-1853

40.00 Set post and drove charred stake for quarter Sec. Cor.
Built mound with trench per instructions. Planted 3 E. Osage
Orange N.E. Apple seed

9/21/92 1/10th North of W1/4 Sec. County Surveyors
dug and found stone 1' x 4' x 4" beside stake
with part of stake still in it. The
mark on top 5" of stone had been cracked & broken
loose, the stone was vertical Drove a 3/8" rod
in stake hole 2 1/2' below the surface of
the ground set two pieces of stone around
this set wood spike @ surface
mark.

6-95 Cedric Found CIM ok 8' South &
Also Found 1 1/4" shaft driven Flush appx
5' So and 1' West of CIM?