6-8-79 CIM

#553504

1/4 corner South 1/4 35 Rock Dell 10S-1S

No apparent records of ever using corner but survey.
P320 no 314 6-1877 by Hunter states in his field book of Sec 2 10S-1S a measure of 4.90 chs that S 1/4 35 lies east of NE cor sec 2. 323.4
This mean not printed in recorded survey 4.90 = ~~653.4~~

9-1853

36.50 Creek 30 lks wide runs S.E.
40.00 Set ▬ Qr Sec. Post
Elm 14 N 84° W 235 lks 155.10 16.12 N. of W
Elm 16 N 17° E 238 lks 157.08 45.93 E of N
46.00 Enter Prairie bears N.W.

1979 Remon. BK., Page 84, 85 6-8-1979

We dug for the corner @ Govt measure from N. 1-2. Appx 1½' deep and in sand subsoil we found a 3" diameter hole of charcoal. We shaved down the side and the charcoal extended down another foot and came to a point. We accepted this as the Govt stake location and drove a ¾" x 3' iron in the center. Set a CIM over the rod. The corner is 1' North of the E-W fence. We set a survey marker sign .85 WSW. Measured 140' E to the West bank of the river.

RP's: Spike & CSD South side blazed 15" Asl WNW 46.38
Spike and CSD East side blazed 14" Asl NNW 101.18
Spike and CSD NW side blazed 7" Elm NE 68.08