#553605

1 6-18-71. found stone in bayou draw, set. iron post Scribe ①

section corner south 35-36 Rock Dell 105-15
6-1878 Hunter P350 no 342 d 1 104-15 J Pierson & others
found stake standing by side of bayou, tested stumps
4 B trees & found correct.
used to set line only for N 1/4 1 104-15
4.80 west 316.80'

5-1895 2r Fraser P574 no 525 d 36 J Pierson & others
stake formed by Hunter washed out by high water.
located corner (a stake & stone) on line N 1/4 1 104-15
4.80 ch 316.8 East and on line with NE cor 1 104-15
now an engraved monument as township corner.
-1/16 north set stake M & L 20.01 1/4 to stone set M & L.

(over)

1/16 east set stake 19.93 N & E. to 2 1/4 36. an iron & wood stake & boulder which lies 4.50 (chuck c Hone) east of NE cor 1 10 4-15 an engraved monument.

4-1906 = 2-1909 Ch Armstrong Pr 106 B - 114 B.
show corners but doubt if ever needed or used.
found 16 corner of NE 1/4 1 (not Hanters stake but granite
boulder. 6 X 16 X 20 at 20.02. 1321.32' not 2010 1326.6

6-17-71 Co surv. ran & meas line from nail at W 1/4 35-36
and nail at NW 36. both center N-S roads. found 1/16 fence with a
prop line mentioned in survey at 1315.3 indicating 00 to far E. 1320.8.
found EW town line fence at 2633.65 under. 00 nail 8' too far E.
- probed for one stone at corner area and 316.8 west for N 1/4 1
found small stone some 8' west of 316.8 area under fence. doubt it.

Card # 2 South 35-36 Rock Dell. 105-15 (2)

6-18-71 Co cor Meas from point near offset NW-6 NE1.
104-14 west found nothing to indicate 1/16 running north,
found stone and fence south at about 1321 R. Hunter 1326.6.
- ac NE1 late found. 2.43 east should accept stone & iron
post, set South of it and put new exact.
- set Nail on ✠ high bank at 2216 + 297 or 2513
- near to W. wire bank Δ to point 90.3 or 2603.3
found stone west 27.2 or 2630.5 R 2630.76
as S 1/4 36 To NW6 actual 295.29 not 297 and.
NW6 2.43 east of nail Meas very near good for wind angle po
- found small stone & small stones under fence west.
- followed N 1/4 1 did not check meas after over

Meas north . 2639.4 to stone at 1/4 35-36
then 2639.65 to stone at N 35-36
corner lies .04' east of direct line as set
found large limestone 2' deep in high water bayou
set steel fence post on S side stone Zero over stone
post has split bottom, will hold in ground well
16 D nail on S side 14" boxelder used as terminal
3' N of E 9.25
9.33
4 fence north & west
-20 Dbn east side of southerly of twin soft Maples S.E. 21.0
21.17
Corner 3'± south of old fence west
8'± west to boxelder terminal end of fence N & W

#553605 (3)

Section Corner South 35-36 Rock Dell 105-15

1979 Remon. BK; Pages 57, 58, 83

Page 58: May 16, 1979 Found the corner found by the County Surveyor in 1971 (a piece of steel fence post over stone - removed). Set a CIC on a 4½' Tetpar on the corner on the North side of the stone (too wet to remove stone since deep and ground very wet - hole filled with water). The corner is 48' West of the W'ly bank of River running NE and SW, 3' South of the fence West and East, and 8' West of the fence North

RP's: - Spike and CSD in E side most N'ly twin large Maple SE 19.13

- spike + CSD E side in S. side Box Elder used as corner post to fence N and E ENE 9.33

Piled boulders on the N. side of mon. And set a survey marker sign & Nail.

Page 83 : 6-8-1979 We dug North of the CIC set @ the S 35-36 for Hunter's corner which was to be on line from the NW Cor 1 on the N¼ Cor 1. There was three feet of creek work and fill to water. We found nothing. We removed the CIC set May 16 and set it 3.41N and .04 W to be on line from NW 1 on N¼ 1 and 4.80 chs. East of N¼ 1 as recorded by Hunter when he had the East stake. The survey sign set May 16 was already gone so we set a new sign 1.95 SE

RP's:- Spike and CSD East side root N'ly twin huge Maple SE 22.30

- Spike and CSD S. side Bot Elder used as corner post to fences N and E E 9.15

We drove a steel fence post at the location of the monument set May 16 at W. Frank's corner.

#553605 (4)

Section Corner South 35-36 Rock Dell 105-15

9-1853

77.70 Creek 75 lks wide runs NE.

80.00 Set Post for corner to Sect. 35 & 36

Ash 10 N 45 E 30 lks

Ash 6 N 89° W 27 lks.