/ #600705

section corner East 12-13 Doner 106-11 & Winona county.
7-1890 Thos Fraser P 444 no 429 & 12 & Co line & earlier & others.
found mound of stones and carefully set stone in center with section numbers on it. no stake below. Corner accepted, so placed triangular boulder 18 x 18 x 18 x 10" thick underneath mound. Corner established and proven by Winona Co. surveyor. Swap line N 10° E

4-1942 J Kerr Winona Book # 1. P. 24.
Meas north from corner found at E 13-24 106-11. 5301.6 to corner. evidently found not described only in drawing & record descriptions.

Gov't Notes: 1853

N. 80.00 chains - Set Post in mound made Trench & Pits & deposited charred stake & Hawthorn Seeds as per instructions

Top dividing ridge - South 25 chains

Oct. 1974 Co. Surveyor
Visited Corner [illegible] Re. post
Probed for Boulder [illegible] many large boulder
down about 2 ft [illegible] Limestone
Set on end [illegible] To be anything
authentic. [illegible]

Fence ~~at~~ at 1/10 North ±1' South and 4' West of ~~stone~~ post. comp. 1/4 cor.

(1305.51 - 1305.51)

By measurements to the 1/4 Sec. from NW 7, W 1/4 7, and SW 7 (as used in the survey), W 7-8 could go 3.6± West