10-23-83 Set 1" sq pipe/cap

#610306

1/4 Corner 3-4 Dover 106-11

GOV. NOTES

South on fence line between sec's 3-4

4.20 Set post at quarter sec corner

made crown of branch & pits &

planted cherry seeds SE, SW, NE, & NW.

10-23-83 Set a 1" sq pipe/cap as corner on line between the sec. corners and in line with fence running East. Corner .85 West of traverse nail in ℄ C.R. 10. Corner in [redacted] road cut so did not dig.

RP's: Punch hole in top South end driveway culvert SE 42.06

C.S. Disc South side of corner post E 49.51

CSD in SE'ly side power pole SW 72.67

The line locations for this corner holds fences at the 1/16 East midway to the 1/4 1/4 Sec 3

Had to choose between fence East and prorated Dont for N-S location, prorated Dont running South

For Prorated: (1) 18.7 Road Surveyor similar proportion
(2) "P @ W 1/4 of over "P @ Cente 4 proj 13.51 So at fence
(3) P @ E 1/4 3 00" "P @ Cente 3 proj 5.91 So at fence

Against Prorated: (1) would be more error in North 1/2 mile (slope)
(2) Would make South 1/2 mile in an area where most mile 1/2 miles are full or long!
(3) Few Final 1/2 miles in this area anywhere near East

For Fence East
(1) Goes with back up property line (R/S plat book)
(2) holds Fence at 1/4 North at exact East prop