¼ Corner 30-31 Ready for CIM Down 106-11

9-28-99 CHC SET 1" SQ PIPE w/CAP #C15004

5-26-77 Surv with backhoe and found a 6"x9"x10" boulder with a flat top 3' deep with a punch stake hub beneath. Set a bolt on the S. side of the stone and a ½"x 1' rod on the N side. Corner 1.0' So & C.R.124 and 3½' East of the fence N and .9' So and 3.55' E of the T.N. Set a ½"x2' rod at the surface.

R.P.s CSD in pp # 1813 NE 133.22

CSD in pp # 1810 NW 124.89

Spike + CSD W side 15" pine SSW 78.08

5-26-77 1/16th East: Surv with the backhoe and found a 5"x 0"/12"x 14" limestone with wood piece and glass 1½' deep. Corner .45' So and .20 W of T.N. and

line with fence N and So. and is ½' S of E.
Set nothing Stone was on line from ¼ Cor 30-31
to NE 31 and .2' W of midway

Feb. 1980 Mike W Found a survey in 1st 100 pages of Book H
That Could be Sec. 30, 10E 11 by Names & Desc of Corners
June 1863 PC Compton Page 71 No 102 (Babbitt & others)
Shows a stone as Corner (5 x 7 x 9)
1/16 east shows stone (5 x 11 x 12)
1/16 north shows stone (5½ x 11 x 20) with Glass beneath

Court Notes William A. Jones
Last on true line between sections 30, 31
39 SC chs set post at ¼ sec corner, made mound,
trench, P.t. & and planted cherry seeds NE, SW, SE, NW

1/4 CORNER 1/4 COR 30-31 DOVER 106-11 #613004 (2)

6-16-95 - FOUND IRON BADLY BENT + LEANING. WE TRIED TO SET UP VERTICAL. BUT IT DID NOT END UP WHERE ANGLE + DIST WOULD PUT IT. WE SET P.K. NAIL @ DISTANCES FROM SEC CORNERS SHOT + .9 SOUTH OF LINE AS PER STONE FOUND IN 1977. THIS FITS THE 1977 TIE TO 15" PINE OF 48.08'. WE GOT 48.09'

6-19-95 - FOUND P.K. SET BY COUNTY SURVEY CREW. SET 1" SQ PIPE W/CAP 40½' NORTH ℄ CR #129.

↑ @ REF PIPE

4 RT PK IN P.P. #1814 TO 1/4 COR 30-31

88° 29' 13" dh 05
0° 42' 49" dh 04
87° 46' 24"

90° 09' 50" dh 03
2° 23' 19" dh 03
87° 46' 31"

TO 1/4 COR 30 31 (P.K NAIL)
VA 85° 50' 56" dv 02
SLOPE 41.38 HOR 41.28

9-20-95 - CHD SET 1" SR PIPE W/CAP