1 9-18-73 set CIM over 3/8 x 24" pipe and stone (1)
Cert 3-6-75 #620104

1/4 corner. 1-12 Eyota 106-12.

6-1875
10-1877 Hunter P281 No 278 & 12. Dr C Zeal, John Bush.

corner missing, extensive search for corner or knowledge of it from settlers to no avail set stake on line & midway 39.73, 2622.18.

Capture — 10-30-1877.

later in 1877 set stone 3 x 6 x 12 with witness stone 50 links north "due north."

1/16 west set stake N & L 19.86 1/2 FBM 11.09 for line south and stake 50 links south as witness + staked fence line S.

9-18-93 dug with tractor after random measurements from stone found at 1-2-11-12 and finding part of witness stone 33' north, found recorded stone 3x6x12 and 2"x18" wood stake on north side of stone. set 3/8"x 24" iron over stone with C/M above. M&L
Measure east and west exact 2621.8. R. 1311.09 E&W
Corner fell 1.0' south of direct line, placed at found
25.89 25.42 (1979) SEly to punch mark in cross top center of 8 end 48" new road Culv.
27.69 27.7 NEly to punch mark in easterly of 2 bg rents in top center N end. 48" road Culv.
gone 49.25 ENE to Cone nail on N side PP # 133.
replaced witness stone exactly 33' north in perfect line of row of power poles — fence north recently removed & leveled

#620104 (2)

¼ Corner 1-12 Eyota 106-12

Set by William Jones 9-1853

West on true line between sect. 1 & 12

39.80 set post at qr section corner deposited charred stake

made mound trench & pits planted cherry seeds SW¼NE

4-13-1979 Found the top part of the CIM @ ¼ Cor 1-12 Eyota broken, so removed the top and first two sections and set a 10" CIM over the remainder. The corner is 2' South of E-W road and 3' West of the fence South

RP's CSD in East side of post NNW 34.65

CSD in N. side pp# 4292.7 ENE 79.31

Punched cross top center S. end 48" CMP SE 25.89
Punch mark in easterly of 2 big rivets
in top center N. end 48" C.M.P. NE 27.69
9/28/92 County Surveyor fd CMP in good
cond.