/ 8-27-73 set CIM over iron rod with old wood stake In Cans glass etc co-1 3-7-75 (1)
#620504

1/4 corner 5-8 Egota 106-12.

5-1877 Hunter P310 no 304 & 8 Mike Cassidy, stat corner missing but fence line north avered as set on line when 1/4 post was standing.. used line of fence north for line south to set center Sec 8. set only temp point

P46B also used fence N to set SES

3-31-1971 Co surv. in search for information on 4-5-8-9. set referenced nail in center crossroads 5270' west of CIM at 3-4-9-10 - R 2628.8 actual 2632.7

- enture 1½ mile CIM at SE4 To fence N at 1/4 5-8 actual 7902.7 R 7889.0

(OVER

8-27-73 dug entire area 8' □ from 5' east to 5' west
℄ fence north - found indications ℄ corner search in
NW side ℄ excavation and one spot dug deep into clay
like wood stake or some definate corner in that area.
- accepted center dug area as corner altho 4' west ℄ fence
north which by edge has definate westward turn further
north as fence runs into brush and trees.
- set CIM over iron, wood stake piece and trash
43.13 SE to Conc nail in PP # 15913 up 2' ±
25.53 4' E ℄ N to conc nail W side old corner post pe N.
118.2 WNW to Conc nail in bottle cap N side tele pole
87.7 SW to center pump standard at spout level.
Meas E to CIM at 4-5-89 Nov 2638.3 ±

(2)

#620504

1/4 Corner 5-8 Eyota 106-12

set by William Joner 9-1853

East on random line

55.50 Brook 5 lks wide runs SW.

West on true line

40.00 Set post at qr sec corner made mound trench & pits planted cherry seeds NE & SW.